

晶体管光耦
Photo Transistor

AT4NXX

Product Data Sheet

AOTE DCC
RELEASE

台湾奥特半导体科技有限公司

TAIWAN AOTE SEMICONDUCTOR TECHNOLOGY CO.,LTD

www.aotesemi.com

概述 Description

AT4NXX是一款由发光二极管和一个光电晶体管组成的光电耦合器。六引脚封装 (DIP6、SMD6)。

The AT4NXX is a photoelectric coupler composed of light-emitting diode and phototransistor. It is packaged in a 6-pin package at DIP、SMD.




特性 Features

- 电流转换比(CTR)范围: $\geq 20\%$ ($I_F = 10\text{mA}$, $V_{CE} = 10\text{V}$, $T_a = 25^\circ\text{C}$) Current transfer ratio: $\geq 20\%$ ($I_F = 10\text{mA}$, $V_{CE} = 10\text{V}$, $T_a = 25^\circ\text{C}$)
- 输入-输出隔离电压 ($V_{ISO} = 5000\text{ Vrms}$)
High isolation voltage between input and output($V_{ISO} = 5000\text{ Vrms}$)
- 输入-输出隔离电阻 (典型值 $R_{iso} = 10^{11}\Omega$)
Input-output isolation voltage resistance ($R_{iso} = 10^{11}\Omega$)
- 工作温度: $-55^\circ\text{C} \sim 100^\circ\text{C}$
Operating Temperature: $-55^\circ\text{C} \sim 100^\circ\text{C}$
- 符合加强绝缘标准
Meet reinforced insulation standards
- 符合安规标准: UL 1577, VDE DIN EN60747-5-5 (VDE 0884-5), CQC11-471543-2022
Meet safety standard approval: UL 1577, VDE DIN EN60747-5-5 (VDE 0884-5), CQC11-471543-2022

应用 Applications

- 电源调节器
Power regulator
- 数字逻辑输入
Digital logic input
- 微处理器输入
Microprocessor input

封装和原理图 Package and Schematic Diagram



Pin Configuration

1. Anode
2. Cathode
3. NC
4. Emitter
5. Collector
6. Base



产品型号命名规则 Order Code


AT 4NXX - UN Y - W (V) (ZZ)

① ② ③ ④ ⑤ ⑥ ⑦

- ① 公司代码 Company Code (AT: 奥特AOTE)
- ② 产品系列 Product Series (XX: 25, 26, 27,28,35,36,37,38)
- ③ 框架类型 Lead Frame (Cu: 铜框架 Copper)
- ④ 树脂类型 Epoxy (H: 无卤 Halogen-free)
- ⑤ 封装形式 Package (D: DIP ; S: SMD)
- ⑥ 器件工作温度范围 Device Operating Temperature Range (特殊范围需填或者空白 Special Range or None)
- ⑦ 内部补充代码 Internal Supplementary Code (数字或者空白 Number or None)

印字信息 Marking Information

- 印字中 “” 为奥特品牌 LOGO
 “” denotes LOGO
- 印字中的 “XX” 代表产品分档 : 25, 26, 27,28,35,36,37,38
 “XX” denotes the classification : 25, 26, 27,28,35,36,37,38
- 印字中 “Y” 代表年份 ; A(2018),B(2019),C(2020).....
 “Y” denotes YEAR : A(2018), B(2019), C(2020).....
- 印字中 “WW” 代表周号
 “WW” denotes Week’ s number
- 印字中 “E” 代表内部代码
 “E” denotes Internal code
- 印字中的 “H” 代表无卤
 “H” denotes Halogen-free



绝缘和安规信息 Insulation and Safety related specifications

| 项目 Item | 符号 Symbol | 数值 Value | 单位 Unit | 备注 Remark |
|---------------------------------------|--------------|-------------|------------|--|
| 爬电距离 Creepage Distance | L | >7.0 | mm | 从输入端到输出端，沿本体最短距离路径 Measured from input terminals to output terminals, shortest distance path along body |
| 电气间隙 Clearance Distance | L | >7.0 | mm | 从输入端到输出端，通过空气的最短距离 Measured from input terminals to output terminals, shortest distance through air |
| 绝缘距离 Insulation Thickness | DTI | > 0.4 | mm | 发射器和探测器之间的绝缘厚度 Insulation thickness between emitter and detector |
| 峰值隔离电压 Peak Isolation Voltage | V_{IORM} | 1500 | V_{peak} | DIN/EN/IEC EN60747-5-5 |
| 瞬态隔离电压 Transient isolation voltage | V_{IOTM} | 7000 | V_{peak} | DIN/EN/IEC EN60747-5-5 |
| 隔离电压 Isolation Voltage | Viso | >5000 | V_{rms} | For 1 min, RH < 60% |

极限参数 Absolute Maximum Ratings (Ta = 25°C)

| 参数 Parameter | | 符号 Symbol | 额定值 Rating | 单位 Unit |
|--|--|--------------|---------------|------------|
| 发射端 Input | 正向电流 Forward Current | I_F | 60 | mA |
| | 峰值正向电流(1us, 脉冲) Peak forward current (1us, pulse) | I_{FP} | 1000 | mA |
| | 反向电压 Reverse Voltage | V_R | 6 | V |
| | 功耗 Power Dissipation | P_D | 100 | mW |
| 接收端 output | 集电极功耗 Collector Power Dissipation | P_C | 300 | mW |
| | 集电极电流 Collector Current | I_C | 100 | mA |
| | 集电极-基极电压 Collector-Base Voltage | V_{CBO} | 70 | V |
| | 集电极-发射极电压 Collector-Emitter Voltage | V_{CEO} | 30 | V |
| | 发射极-集电极电压 Emitter - Collector Voltage | V_{ECO} | 7 | V |
| 总功耗 Total Power Dissipation | P_{tot} | 350 | mW | |
| 输入输出瞬态耐受电压 Input-output isolation voltage | Viso | 5000 | V_{rms} | |
| 工作温度 Operating Temperature | T_{opr} | -55 ~ +100 | °C | |
| 存储温度 Storage Temperature | T_{stg} | -55 ~ +125 | °C | |
| 焊接温度 Soldering Temperature | T_{sol} | 260 | °C | |

产品特性参数 Electro-optical Characteristics (Ta = 25°C)

| 参数 Parameter | | 符号 Symbol | 条件 Condition | 最小 Min. | 典型 Typ. | 最大 Max. | 单位 Unit | |
|-------------------------------------|---|----------------|--|--|--------------------|---------------|---------------|---|
| 发射端 Input | 正向电压 Forward Voltage | V_F | $I_F = 10\text{mA}$ | - | 1.2 | 1.5 | V | |
| | 反向电流 Reverse Current | I_R | $V_R = 3\text{V}$ | - | - | 10 | μA | |
| | 输入电容 Terminal Capacitance | C_t | $V=0, F=1\text{KHz}$ | - | 50 | - | pF | |
| 接收端 Output | 集电极暗电流 Collector Dark Current | I_{CEO} | $V_{CE} = 10\text{V}$ | - | - | 50 | nA | |
| | 集电极-基极击穿电压 Collector-Base Breakdown Voltage | BV_{CBO} | $I_b = 0.1\text{mA}, I_f = 0$ | 70 | - | - | V | |
| | 集电极-发射极击穿电压 Collector-Emitter Breakdown Voltage | BV_{CEO} | $I_c = 0.1\text{mA}, I_f = 0$ | 30 | - | - | V | |
| | 发射极-集电极击穿电压 Emitter-Collector Breakdown Voltage | BV_{ECO} | $I_e = 0.01\text{mA}, I_f = 0$ | 7 | - | - | V | |
| 传输特性 Transfer Characteristics | 电流传输比 Current Transfer Ratio | 4N25、4N26、4N38 | CTR^* | $I_f = 10\text{mA}, V_{CE} = 10\text{V}$ | 20 | - | - | % |
| | | 4N27、4N28 | | | 10 | - | - | % |
| | | 4N35、4N36、4N37 | | | 100 | - | - | % |
| | 集电极-发射极饱和压降 Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_f = 50\text{mA}, I_c = 2\text{mA}$ | - | - | 0.3 | V | |
| | 隔离电阻 Isolation Resistance | R_{ISO} | DC=500V 40~60%R.H. | 5×10^{10} | 1×10^{11} | - | Ω | |
| | 隔离电容 Isolation capacitance | C_{ISO} | $V=0, F=1\text{MHz}$ | - | 1 | 2.5 | pF | |
| | 上升时间 Rise Time | T_r | $V_{CE} = 10\text{V}, I_c = 2\text{mA}, R_L = 100\Omega$ | - | 4 | - | μs | |
| 下降时间 Fall Time | T_f | - | | 3 | - | μs | | |

注*：电流传输比= $I_c/I_f \times 100\%$ 。

Note*：CTR= $I_c/I_f \times 100\%$ 。

典型光电特性曲线 Typical Electro-Optical Characteristics Curves

Fig.1 Relative Current Transfer Ratio vs. Forward Current




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Collector Current vs. Collector-emitter Voltage




Fig.4 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.5 Collector Dark Current vs Ambient Temperature




Fig.6 Response Time vs. Load Resistance




Fig.7 Frequency Response




Fig.8 Collector-emitter Saturation Voltage vs Forward Current






Fig.9 Switching Time Test Circuit & Waveforms




外形尺寸 Outline Dimensions

DIP6




SMD6



单位 Unit: mm

回流焊温度曲线图 Solder Reflow Profile




| 项目 Item | 符号 Symbol | 最小值 Min. | 最大值 Max. | 单位 Unit |
|---|--------------|-------------|-------------|------------|
| 预热温度 Preheat Temperature | T_s | 150 | 200 | °C |
| 预热时间 Preheat Time | t_s | 60 | 120 | s |
| 升温速率 Ramp-Up Rate (T_L to T_P) | - | - | 3 | °C/s |
| 液相线温度 Liquidus Temperature | T_L | 217 | | °C |
| 时间高于 T_L Time Above T_L | t_L | 60 | 150 | s |
| 峰值温度 Peak Temperature | T_P | - | 260 | °C |
| T_c 在 $(T_P - 5)$ 和 T_P 之间的时间 Time During Which T_c Is Between $(T_P - 5)$ and T_P | t_P | - | 30 | s |
| 降温速率 Ramp-down Rate (T_P to T_L) | - | - | 6 | °C/s |

注 Note :

建议在所示的温度和时间条件下进行回流焊，最多不能超过三次；

Reflow soldering is recommended at the temperatures and times shown, no more than three times;

波峰焊温度曲线图 Wave Soldering Profile



手工烙铁焊接 Soldering with hand soldering iron

- A. 手工烙铁焊仅用于产品返修或样品测试；
Hand soldering iron is only used for product rework or sample testing;
- B. 手工烙铁焊要求：温度 $360^{\circ}\text{C} \pm 5^{\circ}\text{C}$ ，时间 $\leq 3\text{s}$ 。
Manual soldering method Temperature: $360^{\circ}\text{C} \pm 5^{\circ}\text{C}$, within 3s.


包装 Packing

■ 汇总表 Summary table

| 封装形式 | 包装方式 | 盘数量 | 盒数量 | 箱数量 | 静电袋规格 | 盒规格 | 箱(双瓦楞)规格 | 备注 |
|--------------|-------------------------------------|-------------------|------------------|---------------------|------------------------------|-------------------|----------------------|---|
| Package Type | Packing Form | Quantity per Reel | Quantity per Box | Quantity per Carton | Antistatic Bag Specification | Box Specification | Carton Specification | Note |
| SMD6 | 卷盘 ($\phi 330\text{mm}$ 蓝盘) | 1000 只/盘 | 2 盘/盒 | 10 盒/箱 | 450*390*0.1mm | 340*60*340mm | 620*360*365mm | 首尾端空至少 200mm |
| DIP6 | 管装 (500*12*11mm) | 65 只/管 | 50 管/盒 | 10 盒/箱 | 不适用 | 525*128*56mm | 535*275*300mm | 每管使用蓝白胶塞, 方向须一致 |
| SMD6 | Reel ($\phi 330\text{mm}$ Blue) | 1000 pcs/reel | 2 reels/box | 10 boxes/ctn | 450*390*0.1mm | 340*60*340mm | 620*360*365mm | Guard band 200mm min. |
| DIP6 | Tube (500*12*11mm) | 65 pcs/tube | 50 tubes/box | 10 boxes/ctn | NA | 525*128*56mm | 535*275*300mm | Endplug (blue) and Endplug (white) keep the direction |


■ 编带包装 Tape & Reel

- 1) 每卷数量：1000 只。
Qty/reel : 1000 pcs.
- 2) 每箱数量：20000 只。
Qty/ctn : 20000 pcs.
- 3) 内包装：每盒 2 盘。
Inner packing : 2 reels/box.
- 4) 示意图 Schematic :



■ 管条包装 Tape & Tube

- 1) 每管数量：65 只。
Qty/Tube : 65 pcs.
- 2) 每箱数量：32500 只。
Qty/ctn : 32500 pcs.
- 3) 内包装：每盒 50 管。
Inner packing : 50 Tube/box.
- 4) 示意图 Schematic



单位/Unit : mm

注意 Attention

- 奥特持续不断改进质量、可靠性、功能或设计，保留此文件更改的权利恕不另行通知。
AOTE continuously improve quality, reliability, function and design. We reserve the right to change this document without prior notice.
- 请遵守产品规格书使用，奥特不对使用时不符合产品规格书条件而导致的质量问题负责。
Please use in accordance with the product specification. AOTE is not responsible for the quality problems caused by non-compliance with the product specifications.
- 对于需要高可靠性或安全性的设备/装置需求，请联系我们的销售人员。
For equipment/devices requiring high reliability or safety, please contact our sales representatives.
- 当需要用于任何“特定”应用时，请咨询我们的销售人员。
When requiring a device for any “specific” application, please contact our sales in advice.
- 如对文件中表述的内容有疑问，欢迎联系我们。
If you have any questions about the contents of the document, please contact us.