


Product Area Male socket, Degree of protec. Without sealing IP 40, with sealing IP 67 (see accessories)  
M12 connectors A-Coding serie 713/763

Pole 4  
Article number 09 3433 00 04


illustration



scale drawing




Contact Arrangement



- 1 braun
- 2 weiß
- 3 blau
- 4 schwarz

Installation instructions / Mounting cutout



Technical data

Common values

Connector Design	Male socket
Connector locking system	Screw-locking
Termination	wires
Wire gauge (mm)	0,25 mm <sup>2</sup>
Wire gauge (AWG)	24
Upper temperature	+85 °C
Lower temperature	-25 °C

Material

Material of contact	CuZn (brass)
Contact plating	Au (gold)
Material of contact body	PA
Material of housing	CUZn (brass nickel plated)

Cable data

Contacts 4: Male socket, with wires 0,25 mm<sup>2</sup>, Degree of protec. Without sealing IP 40, with sealing IP 67 (see accessories)

Electrical values

Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 68
Mechanical operation	>100 mating cycles