



PRODUCT NO.	RoHS compliant
DSDP04LHGETR	

REV.	ECN NO.	DR	DATE




**P.C.B LAYOUT**

- 注意:**
1. 波峰焊: 推荐焊锡温度在270℃±5℃, 浸锡时间为5~6秒钟。
  2. 手工焊: 使用30瓦烙铁控制温度在320℃, 焊接时间大约2~3秒钟。
  3. 拨柄位置: 产品焊接时, 请将产品的拨柄置于OFF端, 能给予产品更好的接触性能。
  4. 清洗过程: 清洗使用超音波方式, 能给予更好的效果。

- Note:**
1. All dimensions are in millimeters.
  2. General tolerance: ±0.2mm.
  3. Material:
    - Base:UL94V-0 PBT Thermoplastic(Black).
    - Cover:UL94V-0 PBT Thermoplastic(Black/Red/Blue).
    - Actuators:UL94V-0 PBT Thermoplastic(White).
    - Contact plating:Gold plating over nickel.
    - Pitting material:Epoxy.
  4. Electrical
    - Electrical:2000 Operations per switch 24/VDC, 25mA.
    - Non-Switching Rating:100mA, 50/VDC.
    - Switching Rating:25mA, 24/VDC
    - Contact Resistance:100 mΩ Max. at initial.
  5. Mechanical
    - Mechanical life:2000 Operations per switch.
    - Stroke:30° .
    - Operation Temp:-20℃ to 70℃.
    - Storage Temp:-40℃ to 85℃.

**6. PART NUMBER DESCRIPTION:**



TOLERANCE UNLESS OTHERWISE SPECIFIED		INSPECTION COPY	东莞市广普实业有限公司 DongGuan Kingtek Industrial Co., Ltd.
LINER	ANGLES		
.0 ± 0.40	0. ± 1'	PROJECTION	TITLE
.00 ± 0.30	.0 ± 0.5'		BY DSDP SERIES PITCH 2.54mm
.000± 0.20	.00±		PRODUCT FAMILY DSDP SERIES
DESIGN LU ER XIN	2013/01/08		PRAT NO. DSDP04LHGETR
DRAWING			FILE NO. DSDP04LHGETR-A
CHECK			SIZE UNIT SCALE SHEET REV.
APPND.			A4 mm FIT 1 OF 1 A