

# EVAL-2QR0665G-28W16V

- [Overview](#)
- [Parametrics](#)
- [Documents](#)
- [Order](#)
- [Boards](#)
- [Support](#)

- [Overview](#)
- [Parametrics](#)
- [Documents](#)
- [Order](#)
- [Boards](#)
- [Support](#)

- [Overview](#)
- [Parametrics](#)
- [Documents](#)
- [Order](#)
- [Boards](#)
- [Support](#)

## Description:

28W 16V Evaluation Board with Quasi-Resonant CoolSET™ ICE2QR0665G

28W switching mode power supply evaluation board designed in a quasi resonant flyback converter topology using **ICE2QR0665G** Quasi-resonant CoolSET™. With the CoolMOS™ integrated in this IC, it greatly simplifies the design and layout of the PCB. Due to valley switching, the turn on voltage is reduced and this offers higher conversion efficiency comparing to fixed frequency hard-switching flyback converter. With the DCM mode control, the reverse recovery problem of secondary rectify diode is relieved. And for its natural frequency jittering with line voltage, the EMI performance is better. Infineon's digital frequency reduction technology enables a quasi-resonant operation till very low load. As a result, the system efficiency over the entire load range is significantly improved compared to conventional free running quasi resonant converter which implements with only maximum switching frequency limitation at light load. In addition, numerous adjustable protection functions have been implemented in ICE2QR0665G to protect the system and customize the IC for the chosen application. In case of failure modes, like open control-loop/over load, output overvoltage, and transformer short winding, the device switches into Auto Restart Mode or Latch-off Mode. By means of the cycle-by-cycle peak current limitation plus foldback point correction, the dimension of the transformer and current rating of the secondary diode can both be optimized. Thus, a cost effective solution can be easily achieved.



## Summary of Features:

- 650V avalanche rugged CoolMOS™ with built in depletion startup cell
- Quasi-resonant operation
- Digital frequency reduction with decreasing load
- Cycle-by-cycle peak current limitation with foldback point correction
- Built-in digital soft-start
- Direct current sensing with internal Leading Edge Blanking Time
- VCC under voltage protection: IC stop operation, recover with softstart
- VCC over voltage protection: IC stop operation, recover with softstart
- Openloop/Overload protection: Auto Restart
- Output overvoltage protection: Latch-off with adjustable threshold
- Short-winding protection: Latch-off
- Over temperature protection: Autorestart

## Target Applications:

set-top box, portable game controller, DVD player, netbook adapter and auxiliary power supply for LCD TV, etc.

## Parametrics

Parametrics	EVAL-2QR0665G-28W16V
Configuration	ICE2QR0665G
Family	CoolSET™
Input Type	AC
Output Current	1.75 A
Output Voltage	16.0 V
P <sub>out</sub>	28.0 W
Product Description	QR CoolSET™ ICE2QR0665G for 28W 16V SMPS evaluation board with 85~265V AC universal input
Qualification	Industrial
Supply Voltage <b>min max</b>	85.0 V 265.0 V
Target Application	Power Supplies
Topology	Flyback
Type	Demo Board

## Documents

[+ Expand all](#)

[+ Product Brief](#)

[+ Application Brochure](#)

## Order

Sales Product Name	EVAL-2QR0665G-28W16V
<b>OPN</b>	EVAL2QR0665G28W16VTOBO1
<b>Product Status</b>	active and preferred
<b>Package name</b>	--
<b>Order online</b>	
<b>Completely lead free</b>	
<b>Halogen free</b>	
<b>RoHS compliant</b>	no
<b>Packing Size</b>	1
<b>Packing Type</b>	CONTAINER

<b>Sales Product Name</b>	<b>EVAL-2QR0665G-28W16V</b>
<b>Moisture Level</b>	
<b>Moisture Packing</b>	NON DRY


## Boards

Board	Family	Description	Status
ICE2QR0665G	CoolSET™		active and preferred

## + Reference Design

## Support

Live Chat Online  
在线支持



Technical Assistance Center  
技术支持中心 (TAC)



Call us Toll Free  
免费热线联系我们



Find an answer to your question

**Please state your question(with at least 3 words)**

### FAQ

- [1. Technical Support \[CN\] \[DE\]](#)
- [2. Chip Card and Security Distis \[CN\] \[DE\]](#)
- [3. HiRel Discretes for special applications, e.g. Aero and Space \[CN\] \[DE\]](#)
- [4. Supplier Service, Supplier Page, page registration \[CN\] \[DE\]](#)
- [5. Use Infineon Designer for Simulation and Development of your Circuit \[CN\] \[DE\]](#)
- [6. How to login to myInfineon \[CN\] \[DE\]](#)

### Technical Assistance Center (TAC)

Infineon welcomes your comments and questions.

If you have any questions concerning our products, please fill out the following form. Your inquiry will be sent to the appropriate specialist who will be in touch with you as soon as possible.

You will receive a confirmation E-mail to validate your address in our system. Any attached file to the reply which will help to support your inquiry is highly appreciated.

First Name\*

Last Name\*

E-Mail\*

Phone

Company\*

Company website (URL)

Industry\*

Other Industry

Country\*

Preferred Distributor / Reseller\*

Other Distributor / Reseller

Product Name\*


Estimated annual production volume (pieces) per year\*

Please post your technical question as detailed as possible\*

I agree that my personal data can be gathered and processed by Infineon Technologies AG and its licensed partners.\*

I would like to receive newsletter informing me about Infineon products. (You can cancel the free subscription any time.)

For more information about our privacy policy please click on [Privacy Policy](#)


































All fields marked with an asterisk (\*) are mandatory.

## Support forum

### Microcontroller

Please visit the Infineon forums: [www.infineonforums.com](http://www.infineonforums.com)

			Last Post
	<b>Microcontroller Forum</b> Microcontroller Forum	 Threads: 2,573 Posts: 8,689	XMC4800 EtherCAT Phy ICs  by aurixuser Nov 3rd, 2017, 11:33 AM
	 <b>XMC Forum</b>	 Threads: 1,880 Posts: 6,909	XMC4800 EtherCAT Phy ICs  by aurixuser Nov 3rd, 2017, 11:33 AM

	<b>XC800 Forum</b>		Threads: 72 Posts: 236	XC886 BSDL File  by or44 Oct 19th, 2017, 04:07 AM
	<b>XE166/XC2000 Forum</b>		Threads: 164 Posts: 490	Problem with the FIFO using...  by Isnochys79 Oct 20th, 2017, 07:51 AM
	<b>TriCore Forum</b>		Threads: 355 Posts: 878	AURIX TC23x Standby Mode  by a.montesinos Nov 3rd, 2017, 01:36 AM
<b>Last Post</b>				
	<b>DAVE™ Forum</b> DAVE™ Forum		Threads: 1,357 Posts: 5,325	Using Dave 3 with custom HW  by gianmario Nov 3rd, 2017, 11:48 AM
<b>Last Post</b>				
	<b>POWER MOSFET</b> Infineon's whole range of power MOSFETs and systems enable innovation and performance in your application, like switch mode power supplies (SMPS), computing, motor control and drives, consumer, mobile devices, lighting solutions, automotive and more. Welcome to the Infineon MOSFET Forum. We encourage you to post some of your design challenges and start using the forum to receive support from the community.		Threads: 68 Posts: 157	why IR3475MTRPBF lost output ?  by david888 Oct 22nd, 2017, 06:46 PM
<b>Last Post</b>				
	<b>Applications</b> Applications		Threads: 34 Posts: 101	HOWTO start - step by step  by FuckYou Oct 27th, 2017, 06:46 AM
	<b>iMOTION™ MADK Platform</b> Complete and scalable system solution for motor drives. Get a Motor running in less than 1 hour with a compact and flexible 3-phase motor drive evaluation platform with controller & IPM, sensorless or optional with sensors.		Threads: 12 Posts: 31	What's the purpose of EEPROM...  by Williamsk Jun 20th, 2017, 04:19 AM
	<b>Multicopter</b> Ready-to-use multicopter solutions that includes every essential semiconductor, from power electronics, to controllers, to securities, to authentication, to sensors.		Threads: 20 Posts: 68	HOWTO start - step by step  by FuckYou Oct 27th, 2017, 06:46 AM

Follow us



© 1999 - 2017 Infineon Technologies AG, 苏ICP备15016286号

> Usage of this website is subject to our Usage Terms > Imprint > Contact > Privacy Policy > Glossary

> Switch to Mobile Version

In order to optimize your browsing experience Infineon uses cookies. You agree to the usage of cookies when you continue browsing this site. Please read our > **Privacy Policy** for more information.

OK