




Connectors > PCB Connectors > PCB Headers & Receptacles > SUPERSEAL Connector Headers: 1.0 mm



Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 60

Centerline (Pitch): 3 mm, 3.5 mm [.118 in, .138 in]

Sealable: Yes

PCB Mount Orientation: Right Angle

[All SUPERSEAL Connector Headers: 1.0 mm \(23\)](#)

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Header Type	Fully Shrouded
Connector System	Wire-to-Board, Wire-to-Device
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Signal Positions	60
Number of Positions	60
PCB Mount Orientation	Right Angle
Number of Rows	4



Electrical Characteristics

Voltage Rating (Max)	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 42 V, 48 V, 240 V
Operating Voltage	250 VAC

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Size	1mm
Contact Type	Pin
Mating Pin Diameter	1 mm[.039 in]
Contact Mating Area Plating Material	Gold

Termination Features

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Mechanical Attachment

Mounting Holes	With
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Locking Interface
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	3 mm, 3.5 mm[.118 in][.138 in]
--------------------	--------------------------------

Dimensions

Connector Length	78 mm[3.07 in]
Connector Width	23 mm[.906 in]
Profile Height from PCB	21.4 mm[.843 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]

Operation/Application



Shielded	No
----------	----

Industry Standards

Degree of Protection	JIS D0203
----------------------	-----------

Packaging Features

Packaging Quantity	320
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




Also in the Series | **SUPERSEAL 1.0mm**




Automotive Housings(14)



Automotive Terminals(6)



Connector Backshells(2)



Connector Seals & Cavity Plugs(1)



PCB Headers & Receptacles(33)

Customers Also Bought



TE Part #3-1437290-9
34POS,SUPERSEAL,REC HSG ASSY,
SLD,COD 2



TE Part #9-6437287-8
SUPERSEAL Connector Headers: 1.0
mm



TE Part #1-967658-1
8pos MQS .63 header 90deg




TE Part #175785-1
Low & Medium Power Header



TE Part #1376886-1
3900281-442=S/S PLUG ASSY 44P



TE Part #174985-7
8 POS. DL PLATE FOR CAP MK II+



TE Part #3-1617109-8
SMGSD-8013 = SMGSD SURF.
MOUNT



Documents

Product Drawings

SUPER SEAL 60POS CAP ASSY H AU

Japanese

SUPER SEAL 60POS CAP ASSY H AU

English

CAD Files

Customer View Model

ENG_CVM_CVM_3-6437285-2_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-6437285-2_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-6437285-2_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

Product Specifications

Receptacle Contact, Super Seal Connector

Japanese

Application Specification

Japanese

Super Seal Connector

Japanese

Application Specification

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

English

SUPER SEAL CONNECTOR PLUG HOUSING CONNECTOR

English

Agency Approvals

UL Report

English

3-6437285-2

PCB Mount Header, Right Angle, Wire-to-Board / Wire-to-Device, 60 Position, 3 mm / 3.5 mm [.118 in / .138 in] Centerline, SUPERSEAL 1.0mm

