



ZLTMM-112-75-L-D-285



(2.00 mm) .0787"

LTMM, ZLTMM SERIES

# SHROUDED HEADER & STACKER

Mates with:  
SQT, SQW, ESQT, SMM

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?LTMM](http://www.samtec.com?LTMM) or [www.samtec.com?ZLTMM](http://www.samtec.com?ZLTMM)

**Insulator Material:**  
Black Liquid Crystal Polymer  
**Terminal Material:**  
Phosphor Bronze

**Plating:**

Sn or Au over  
50 μ" (1.27 μm) Ni

**Operating Temp Range:**  
-55 °C to +105 °C with Tin;  
-55 °C to +125 °C with Gold

**RoHS Compliant:**  
Yes

## PROCESSING

**Lead-Free Solderable:**  
Yes

**SMT Lead Coplanarity:**  
(0.10 mm) .004" max

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



<b>LTMM</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>02</b>	<b>PLATING OPTION</b>	<b>D</b>	<b>TAIL OPTION</b>	<b>OTHER OPTION</b>
<p><b>04, 05, 06, 07, 08, 10, 12, 13, 15, 17, 20, 22, 25</b> (Standard sizes)</p>				<p><b>-F</b> = Gold flash on post, Matte Tin on tail</p> <p><b>-L</b> = 10 μ" (0.25 μm) Gold on post, Matte Tin on tail</p> <p><b>-T</b> = Matte Tin</p>	<p>Leave blank for Through-hole</p> <p><b>-RA</b> = Right-angle</p> <p><b>-SM</b> = Surface Mount</p>	<p><b>-“XX”</b> = Polarized Position</p> <p><b>-LC</b> = Locking Clip (-SM only) (Manual placement required)</p> <p><b>-K</b> = (7.50 mm) .295" DIA Film Pick &amp; Place Pad (-SM only)</p> <p><b>-TR</b> = Tape &amp; Reel (-SM only)</p>	
<b>OTHER SOLUTIONS</b>		<b>OTHER OPTION</b>					

## OTHER SOLUTIONS

- Shrouded IDC headers and stackers to mate with TCSD Series. See STMM and ZSTMM Series.

## ALSO AVAILABLE (MOQ Required)

- Other sizes
- Other platings

**Note:**  
This Series is non-standard, non-returnable.

<b>ZLTMM</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>LEAD STYLE</b>	<b>PLATING OPTION</b>	<b>D</b>	<b>BODY HEIGHT</b>	<b>OTHER OPTION</b>
<p><b>04, 05, 06, 07, 08, 10, 12, 13, 15, 17, 20, 22, 25</b> (Standard sizes)</p>				<p>Specify LEAD STYLE from chart.</p>	<p><b>-F</b> = Gold flash on post, Matte Tin on tail</p> <p><b>-L</b> = 10 μ" (0.25 μm) Gold on post, Matte Tin on tail</p> <p><b>-T</b> = Matte Tin</p>	<p><b>-“XXX”</b> = Body Height</p> <p><b>-“XX”</b> = Polarized Position</p>	
<b>OTHER SOLUTIONS</b>		<b>OTHER OPTION</b>					

LEAD STYLE	B (OAL)	MAX BODY HEIGHT
-75	(9.58) 0.377	(7.42) 0.292
-62	(10.08) 0.397	(7.92) 0.312
-65	(10.49) 0.413	(8.33) 0.328
-73	(12.09) 0.476	(9.93) 0.391
-63	(14.10) 0.555	(11.94) 0.470
-66	(15.09) 0.594	(12.93) 0.509
-69	(15.60) 0.614	(13.44) 0.529
-74	(17.09) 0.673	(14.94) 0.588
-70	(17.60) 0.693	(15.44) 0.608
-71	(21.08) 0.830	(18.92) 0.745
-72	(21.62) 0.851	(19.46) 0.766

**Note:** For added mechanical stability, Samtec recommends mechanical board spacers be used in applications with gold or selective gold plated connectors. Contact [ipg@samtec.com](mailto:ipg@samtec.com) for more information.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Samtec:

[LTMM-110-02-G-D](#) [LTMM-120-02-L-D](#) [LTMM-107-02-G-D](#) [LTMM-107-01-G-D-SM](#) [LTMM-125-02-L-D](#) [LTMM-120-02-L-D-RA](#) [LTMM-112-02-L-D-SM](#) [LTMM-105-02-F-D](#) [LTMM-105-02-G-D](#) [LTMM-107-02-F-D](#) [LTMM-112-02-L-D](#) [LTMM-105-02-T-D-RA](#) [LTMM-107-02-G-D-SM](#) [LTMM-105-02-L-D](#) [LTMM-110-02-L-D](#) [LTMM-110-02-T-D](#) [LTMM-108-02-G-D](#) [LTMM-107-02-L-D-SM](#) [LTMM-104-02-F-D](#) [LTMM-107-02-G-D-RA](#) [LTMM-115-02-F-D](#) [LTMM-122-02-T-D](#) [LTMM-108-02-G-D-SM](#) [LTMM-107-02-L-D](#) [LTMM-107-02-S-D](#) [LTMM-113-02-S-D-SM-K](#) [LTMM-125-02-G-D](#) [LTMM-110-02-G-D-RA](#) [LTMM-115-02-L-D-SM-K-TR](#) [LTMM-110-02-G-D-18](#) [LTMM-110-02-G-D-17](#) [LTMM-115-02-F-D-SM-LC](#) [LTMM-125-02-F-D-SM](#) [LTMM-115-02-T-D-SM-K-TR](#) [LTMM-117-02-F-D-SM-K](#) [LTMM-122-02-L-D-SM-K](#) [LTMM-125-02-G-D-36](#) [LTMM-112-02-F-D-SM-LC](#) [LTMM-113-02-L-D-SM-K](#) [LTMM-122-01-G-D-SM-P-TR](#) [LTMM-111-02-S-D-SM](#) [LTMM-110-02-G-D-05](#) [LTMM-115-02-F-D-SM-K](#) [LTMM-117-02-F-D-SM-LC](#) [LTMM-117-02-T-D-SM-K](#) [LTMM-106-02-T-D-SM-TR](#) [LTMM-107-01-G-D-SM-K-TR](#) [LTMM-115-02-L-D-SM-K](#) [LTMM-120-02-F-D-SM-LC](#) [LTMM-110-02-L-D-SM-TR](#) [LTMM-112-02-F-D-SM](#) [LTMM-110-02-H-D-SM-TR](#) [LTMM-104-02-F-D-SM-TR](#) [LTMM-110-02-L-D-SM-20-TR](#) [LTMM-107-02-L-D-SM-01-K](#) [LTMM-102-02-L-D-SM-K-TR](#) [LTMM-112-02-S-D-SM-K-TR](#) [LTMM-112-02-L-D-SM-LC](#) [LTMM-122-02-F-D](#) [LTMM-108-02-G-D-SM-P-TR](#) [LTMM-113-02-S-D-SM](#) [LTMM-108-02-T-D](#) [LTMM-115-02-G-D-SM-LC-TR](#) [LTMM-104-02-S-D](#) [LTMM-105-02-T-D-SM](#) [LTMM-106-02-G-D-RA](#) [LTMM-106-02-T-D-06](#) [LTMM-108-01-S-D](#) [LTMM-110-02-S-D-SM](#) [LTMM-113-02-G-D](#) [LTMM-113-02-G-D-SM](#) [LTMM-113-02-T-D](#) [LTMM-115-02-G-D-SM](#) [LTMM-104-02-S-D-RA](#) [LTMM-105-01-F-D](#) [LTMM-105-02-G-D-SM](#) [LTMM-104-02-G-D-SM](#) [LTMM-107-01-G-D-RA](#) [LTMM-108-02-T-D-SM-K-TR](#) [LTMM-113-02-S-D-SM-LC-TR](#) [LTMM-117-02-T-D-21](#) [LTMM-122-02-L-D-RA](#) [LTMM-122-02-T-D-RA](#) [LTMM-113-02-G-D-SM-K](#) [LTMM-117-02-S-D-SM-LC](#) [LTMM-125-02-G-D-SM-K](#) [LTMM-105-01-S-D-SM-LC-TR](#) [LTMM-110-02-G-D-SM](#) [LTMM-110-02-L-D-SM](#) [LTMM-115-02-S-D-SM-LC-K-TR](#) [LTMM-125-02-G-D-SM](#) [LTMM-105-01-S-D-RA](#) [LTMM-105-01-L-D-RA](#) [LTMM-105-02-G-D-SM-P](#) [LTMM-106-01-L-D-SM](#) [LTMM-106-02-G-D](#) [LTMM-108-02-G-D-SM-LC](#) [LTMM-108-02-S-D](#) [LTMM-110-01-G-D](#) [LTMM-110-02-S-D-RA](#)