

# CGS | CGS SMQ

TE Internal #: 5-2176620-2

Power Resistor, Metal Film, 3 W, 68K ohm, 5 %, ±100 ppm/°C, Solder, 2 Termination, Height 6.8 mm [.268 in], Length 13.5 mm [.

531 in], CGS SMQ

View on TE.com >



Passive Components > Resistors > Surface Mount Resistors











Resistor Type: Power Resistor

Element Type: Metal Film

Power Rating: 3 W

Resistance Value:  $68K\Omega$ 

Resistance Class:  $1k\Omega - 1M\Omega$ 

### **Features**

# **Product Type Features**

Surface Mount Resistor Termination Type

Number of Terminations

Resistor Type	Power Resistor
Element Type	Metal Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Operating Voltage	500 V
Power Rating	3 W
Resistance Value	68K Ω
Resistance Class	$1k\Omega - 1M\Omega$
Passive Component Tolerance	5 %
Termination Features	

Solder

2



#### **Dimensions**

Product Height	6.8 mm[.268 in]
Product Length	13.5 mm[.531 in]
Product Width	7.3 mm[.287 in]

# **Usage Conditions**

Operating Temperature Range	-55 – 150 °C
Temperature Coefficient	±100 ppm/°C

# **Industry Standards**

Moisture Sensitivity Level	1
ESD HBM Classification	2
Industry Standard	AEC-Q200 Compliant
UL Flammability Rating	UL 94V-0

### **Packaging Features**

Packaging Method	Taped & Reeled

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

Power Resistor, Metal Film, 3 W, 68K ohm, 5 %, ±100 ppm/°C, Solder, 2 Termination, Height 6.8 mm [.268 in], Length 13.5 mm [.531 in], CGS SMQ



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.


# Compatible Parts







# Also in the Series | CGS SMQ



# **Documents**

Product Drawings SMQF3W 68K 5%

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_5-2176620-2\_BA.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-2176620-2\_BA.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-2176620-2\_BA.3d\_stp.zip

English

Power Resistor, Metal Film, 3 W, 68K ohm, 5 %,  $\pm 100$  ppm/°C, Solder, 2 Termination, Height 6.8 mm [.268 in], Length 13.5 mm [.531 in], CGS SMQ



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages
SMD\_MOULDED\_POWER\_RESISTOR

English