6GK5108-0BA00-2AC2

# **Data sheet**





SCALANCE XC108, Unmanaged IE switch, 8x 10/100 Mbit/s RJ45 ports, LED diagnostics, error-signaling contact with set pushbutton, redundant power supply Manual available as a download .



product type designation	
product brand name	SCALANCE
product type designation	XC108
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	8; RJ45
interfaces / other	
number of electrical connections	
<ul> <li>for signaling contact</li> </ul>	1
for power supply	1
type of electrical connection	
<ul> <li>for signaling contact</li> </ul>	2-pole terminal block
for power supply	4-pole terminal block
operating voltage / of the signaling contacts	
at DC / rated value	24 V
operational current / of the signaling contacts	
at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V
<ul><li>power loss [W] / 1 / rated value</li></ul>	3 W
<ul> <li>supply voltage / 1 / rated value</li> </ul>	9.6 31.2 V
<ul><li>consumed current / 1 / maximum</li></ul>	0.25 A
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
<ul> <li>fuse protection type / 1 / at input for supply voltage</li> </ul>	2.5 A / 125 V
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	-40 +70 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
$\bullet$ at 25 $^{\circ}\text{C}$ / without condensation / during operation / maximum	95 %

protection class IP	IP20
design, dimensions and weights	11 20
design	compact 60 mm
width	60 mm
height	147 mm 125 mm
depth	
net weight	0.475 kg
material / of the enclosure	Polycarbonate (PC-GF10)
fastening method	V
35 mm top hat DIN rail mounting	Yes
wall mounting	Yes
S7-300 rail mounting     S7-4500 rail mounting	Yes
• S7-1500 rail mounting	Yes
product features, product functions, product components / gene	
number of automatically learnable MAC addresses	2048
product functions / management, configuration, engineering	
product function	
multiport mirroring	No
• CoS	Yes
• switch-managed	No .
PROFINET conformity class	A
product functions / redundancy	
product function	
Parallel Redundancy Protocol (PRP)/operation in the  PRP patriorly.	Yes
PRP-network	Na
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
standards, specifications, approvals	
certificate of suitability	
• CE marking	Yes
• EC Declaration of Conformity EN 61010, IEC 61010-1,	Yes
UL 61010A-1	
<ul> <li>KC approval</li> </ul>	Yes
<ul> <li>Regulatory Compliance Mark (RCM)</li> </ul>	Yes
standard	
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
standards, specifications, approvals / hazardous environments	
certificate of suitability	
• ATEX	Yes
• UKEX	Yes
• IECEx	Yes
ULhazloc approval	Yes
CCC / for hazardous zone according to GB standard	Yes
FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
• E1 approval	Yes
RoHS conformity	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
American Bureau of Shipping Europe Ltd. (ABS)	Yes
French marine classification society (BV)	Yes
• DNV GL	Yes
Korean Register of Shipping (KRS)	Yes
Lloyds Register of Shipping (LRS)	Yes
Nippon Kaiji Kyokai (NK)	Yes
Polski Rejestr Statkow (PRS)	Yes
Royal Institution of Naval Architects (RINA)	Yes
standards, specifications, approvals / Environmental Product Do	***
Siemens Eco Profile (SEP)	Siemens EcoTech
Environmental Product Declaration	Yes
Environmental i roduct Decidiation	100

Global Warming Potential [CO2 eq] 153.7 kg • during manufacturing 28.4 kg during operation 125.2 kg • after end of life 0.02 kg product functions / general laser protection class LED Class 1 reference code • according to IEC 81346-2 KF • according to IEC 81346-2:2019 **KFE** 5 a Warranty period product function / is supported / identification link Yes; according to IEC 61406-1:2022 further information / internet links internet link • to website: Selection guide for cables and connectors https://support.industry.siemens.com/cs/ww/en/view/109766358 • to web page: selection aid TIA Selection Tool https://www.siemens.com/tstcloud • to website: Industrial communication https://www.siemens.com/simatic-net • to web page: SiePortal https://sieportal.siemens.com/ • to website: Image database https://www.automation.siemens.com/bilddb • to website: CAx-Download-Manager https://www.siemens.com/cax • to website: Industry Online Support https://support.industry.siemens.com

### security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

## Approvals / Certificates

## **General Product Approval**



Declaration of Conformity





Miscellaneous



**EMV** For use in hazardous locations **Test Certificates** <u>KC</u> <u>FM</u> CCC-Ex inspection certificate

IECEx



#### Marine / Shipping









NK / Nippon Kaiji Kyokai



Industrial Commu-Marine / Shipping **Environment** nication



Confirmation





**PROFINET** 

last modified: 6/3/2024 🖸