



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00424	Connector, USB A receptacle	1	
2	50-00428	Connector, USB A micro male	1	
3	30-00088	Wire, 4C, 1PR + 2C, 28 AWG, UL2725, 30V, 80C, 3.6 mm, shielded, VW-1, PVC, 79A, USB 2.0	1	
4	24-00058	Overmold, PVC, black	1	
5	24-00064	Overmold, PVC, black	1	
6	Label 649	Adhesive, flag, 10x60 mm	1	



Notes:

Cables individually tied and bundled in groups of 10
 Functionally equivalent components may be substituted



Wiring diagram		
50-00424	Wire Color	50-00428
1	Red	1
2	White	2
3	Green	3
4	Black	4 & 5
Shell	Drain & Shield	Shell


Revision:	Date:	Description:	Prepared:	Notes: RoHS and REACH compliant
A	8/24/2011	Initial release	Verified:	
A1	1/28/2014	Corrected shield type	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	
			Description:	Cable, 100 mm, USB A receptacle to USB A micro male, 28 AWG, 30-00088 wire

TENSILITY

tel 1.541.323.3228 800 877.670.7118
 fax 1.541.323.4202 web tensility.com

Size: A
 Part number: 10-00649

Scale: 1:1



Sheet 1 of 1