

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.11.11	阿树

(无缺、防呆)

REFERENCE WATING INTERFACE PATTERN:
1.27 SRAGGERED PITCH x 1.5
ROW-DISTANCE.

POLARISATION
SOLT

0.10

1.27x1.5MM SMT母头
(有耳/有台/单缺/SMT)

PCB Layout

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAuces	



PART NO.:

X9127 W V S-XX B-9T SN XX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ①Series No
- ②Category:W-Wafer
- ③Welding Board Angle:V-Stright 180°
- ④Welding Way: S-SMT
- ⑤Row No.Pin No:XX-04~26Pin
- ⑥Plug the Pin & Special No.:
B-With boss and tail, With Ear, Concave
- ⑦Material: 9T-Nylon 9T 94V-0
- ⑧Plating Category: SN-Bright tin Plating
- ⑨Color: RE-Red RD-purplish red

■SPECIFICATIONS

- Voltage rating:500V AC/DC
- Current rating:1A AC/DC
- Withstanding Voltage:1000V AC/minute
- Temperature range:-40°C~+125°C
- Insulation resistance:≥1000MΩ
- Contact resistance: ≤20mΩ
- After environment testing: ≤30mΩ

Poles	Dimensions(mm)			Q'ty/Tube
	A	B	C	
4	3.81	5.50	9.71	59
6	6.35	8.04	12.25	47
8	8.89	10.58	14.79	39
10	11.43	13.12	17.33	33
12	13.97	15.66	19.87	29
14	16.51	18.20	22.41	25
16	19.05	20.74	24.95	23
18	21.59	23.28	27.49	21
20	24.13	25.82	30.03	19
22	26.67	28.36	32.57	17
24	29.21	30.90	35.11	16
26	31.75	33.44	37.65	15

X9127WVS-XXB-9TSNRD	Purplish red	PA9T UL 94V-0	Brass	Tin-Plated
X9127WVS-XXB-9TSNRE	RED			
PART NO	Color	Material	Material(Pin)	Finish(Pin)

DESIGN	阿树	VIEW:	MODEL TYPE: 1.27mm Crimp Style Connectors
CHECKED		UNIT: mm/in	PART NO.: X9127WVS-XXB-9TSNXX
APPROVED		SIZE: A4	DWG NO.: