|   | home   | imprint   | conta                 | act terms         | and conditions  | sitemap         |
|---|--|-----------|-----------------------|-------------------|-----------------|-----------------|
| main menue  | Home crocodile clips 4                           | mm system | crocodile clips       | 4 mm system       | AK 10           |                 |
| home<br>test & measurement<br>download                          | AK 10  |           |                       |                   |                 |                 |
| online catalogue T&M  | datasheet for AK 10<br>article number: 930126102 |           |                       |                   |                 | S               |
| crocodile clips<br>0,64 mm system<br>2 mm system<br>4 mm system | View Full-Size Image                             |           |                       |                   |                 | SKS Kontaktted  |
| 4 mm safety system  | product description:                             |           | order number: 930     | 126-102           |                 |                 |
| test probes   | description:                                     |           | Insulated alligator o | lin Clamping rang | re un to 6 mm l | oolt diameter F |

| test probes<br>oscilloscope test probes | description:              | Insulated alligator clip. Clamping range up to 6 mm bolt diameter. Fi<br>section for very thin wires. Only the lower part o fthe clip has a tin-p<br>contact insert. 4 mm diameter socket connection. |  |  |
|---|---------------------------|---|--|--|
| measuring leads                         | typ:                      | AK 10 blau/blue   |  |  |
| plugs                                   | system:                   | 4 mm system   |  |  |
| sockets                                 | order number:             | 930 126-102   |  |  |
|   | clamping range:           | 6 mm  |  |  |
| sets                                    | color versions:           |   |  |  |
| miscellaneous                           |                           |   |  |  |
|   | technical data            |   |  |  |
| Search                                  | type of contact:          | socket  |  |  |
|   | type of termination:      | 4 mm socket   |  |  |
| Search                                  | rated voltage:            | DC 60 V   |  |  |
| •                                       | rated current:            | 6 A   |  |  |
| company                                 | contact resistance:       | 15 mOhm   |  |  |
|   | material                  |   |  |  |
| corporate association                   | contact material:         | brass   |  |  |
|   | contact surface material: | tinned  |  |  |
| location maps                           | housing material:         | PS  |  |  |
| fairs and exhibitions                   | environmental conditions: |   |  |  |
| jobs                                    | temperature range:        | -25 °C to +60 °C  |  |  |
|   | inflammable class:        |   |  |  |
|   | housing:                  | 94 HB   |  |  |
|   | drawing                   |   |  |  |

