

Datasheet for 76650-0029

General Informatio	General Information				
Part Number:	76650-0029				
Manufacturer:	Molex / Waldom				
Title:	Solderless Terminal Kit Asserted Nep Insulated Quick Disconnect, Ping, Spade and Butt Splice Solderless				
Description:	Assorted Non-Insulated Quick Disconnect, Ring, Spade and Butt Splice Solderless Terminals. Nylon Insulated Closed-End Solderless Terminals, with Universal Crimping Tool				
Product Family:	Solderless Terminals				
Certificates:	(Molex Parts within this kit) - EU RoHS Compliant and UL				
Country of Origin:	Kit assembled in U.S.A.				
Specifications					
Design					
Configuration:	Wire-to-Wire, Wire-to-Board / Solderless Terminals				
Size(s):	.250", # 6 and # 10				
Current Rating:	Per (Proper) Wire Specification				
Voltage:	Per (Proper) Wire Specification				
Wire size:	(22-18) and (16-14)				
Product Highlights					

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.

Spades have the open tongue end used for rapid insertion on the mounting screw. The spade is usually used on free standing studs.

Butt Splices allow two stripped wires to be inserted into each end and "butt" in the center, with the crimp securing both wires together.



Datasheet for 76650-0029

Features and Benefits	Applications
 Terminals employ the full barrel length that eliminates costly and time consuming location when crimping Finest quality electrolytic copper One-piece design, butted seam The Spade's open tongue end is for rapid insertion on the mounting screw / stud The basic Ring Tongue type is the safest and most reliable because it cannot be disconnected unless the screw is completely removed. Block Spades are designed for use in terminal blocks 	 MRO (Maintenance Repair and Operations) Consumer applications Power applications Motor applications Powertrains Transportation Construction / Mining Energy / Power Production Equipment Instrumentation Environmental Equipment and Controls Blower Motors



Datasheet for 76650-0029

Bill of Materials for Part No. 76650-0029

Molex Part No.	Country of Origin	Description	Quantity in Kit
19016-0111	USA	Non-insulated .250" Female Quick Disconnects,16-14 AWG	40
19022-0018	USA	Non-insulated .250" Male Quick Disconnects, 16-14 AWG	40
19044-0032	USA	Non-insulated #10 Ring Tongue Terminals, 16-14 AWG	30
19044-0068	USA	Non-insulated #6 Ring Tongue Terminals, 22-18 AWG	30
19044-0072	USA	Non-insulated #10 Ring Tongue Terminals, 22-18 AWG	30
19044-0152	USA	Non-insulated #6 Ring Tongue Terminals, 16-14 AWG	30
19118-0021	USA	Non-insulated #6 Flanged Block Spade Terminals, 22-18 AWG	40
19128-0021	USA	Non-insulated #6 Block Spade Terminals, 16-14 AWG	30
19146-0037	USA	Non-insulated #10 Block Spade Terminals, 16-14 AWG	30
19160-0002	USA	Insulated Nylon Closed-end Connectors, 16-14 AWG	20
19189-0002	USA	Non-insulated Butt Splice Connectors, 22-18 AWG	40
19189-0008	USA	Non-insulated Butt Splice Connectors, 16-14 AWG	40
CT-4071-1R^	Taiwan	Universal Hand Crimping Tool, 22-10 AWG	1

Recommended Molex Tool(s) for Part No. 76650-0029*

Country	
of Origin	Description
USA	Hand Crimp Tool (RHT-7000)
USA	Hand Crimp Tool (RHT-1992)
USA	Hand Crimp Tool (RHT-1752)
	of Origin USA USA

*Tool(s) not included in kit. Tool(s) ordered separately.