

3208074
<https://www.phoenixcontact.com/us/products/3208074>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Module socket contact, inserted in the PCC or HCC plug housing after crimping the conductor, for 1 mm² ... 2.5 mm² conductors, ribbon contact

Commercial data

Item number	3208074
Packing unit	3,500 pc
Minimum order quantity	3,500 pc
Product key	AACCEG
GTIN	4046356166584
Weight per piece (including packing)	0.76 g
Weight per piece (excluding packing)	0.76 g
Country of origin	CZ

STG-MTN 1,0-2,5 CUFE2 LU - Crimp contact



3208074

<https://www.phoenixcontact.com/us/products/3208074>

Technical data

Product properties

Product type	Connector
Product family	MSTBC-MT
Pitch	0 mm

Dimensions

Pitch	0 mm
-------	------

Material specifications

Contact surface	Tin Sn
-----------------	--------

STG-MTN 1,0-2,5 CUFE2 LU - Crimp contact



3208074

<https://www.phoenixcontact.com/us/products/3208074>

Classifications

ECLASS

ECLASS-11.0	27469090
ECLASS-13.0	27469090
ECLASS-12.0	27469090

ETIM

ETIM 9.0	EC002943
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

STG-MTN 1,0-2,5 CUFE2 LU - Crimp contact



3208074

<https://www.phoenixcontact.com/us/products/3208074>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

STG-MTN 1,0-2,5 CUFE2 LU - Crimp contact



3208074


<https://www.phoenixcontact.com/us/products/3208074>

Accessories

PCC 4/ 2-ST-7,62 - PCB connector

1840191

<https://www.phoenixcontact.com/us/products/1840191>



PCB connector, nominal cross section: 4 mm², color: green, nominal current: 20 A, rated voltage (III/2): 1000 V, contact connection type: Socket, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: PCC 4/..-ST, pitch: 7.62 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON PC 4, locking: without, mounting: without, type of packaging: packed in cardboard, Corresponding female crimp contacts with current [A] and conductor cross section range [mm²] data: 13,5A/STG-MTN 0,5-1,0 (3190438); 13,5A/STG-MTN 0,5-1,0 BA (3190629); 20A/STG-MTN 1,5-2,5 (3190506); 20A/STG-MTN 1,5-2,5 BA (3190632). BA = Taped contacts

ST-IL - Mounting material

3039900

<https://www.phoenixcontact.com/us/products/3039900>

Operating decal for the ST terminal block



STG-MTN 1,0-2,5 CUFE2 LU - Crimp contact




3208074

<https://www.phoenixcontact.com/us/products/3208074>

CEC 2,5 - Filler plug

3062757

<https://www.phoenixcontact.com/us/products/3062757>



Cover for conductor shaft, 10-pos., for spring cage terminal blocks (ST) and terminal blocks with push-in technology (PT) with a width of 5.2 mm

WST 2,5 - Warning cover

3030941

<https://www.phoenixcontact.com/us/products/3030941>



Warning cover, 5-pos., for terminal width: 5.2 mm

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com