

LFB1X2G45CN3E016

In Production **Recommended** **RoHS** **REACH**

Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	180mm Paper Tape	4000

Features

Ultra-small, low-profiled, lightweight chip filters based on ceramic multilayer technology.
Extremely ultra-small band-bass filters.

1. Ultra-small, low-profiled, lightweight band-pass filters.
2. Absolutely no adjustment required.
3. Reflow solderable.
4. Available in tape and reel packagings for automatic mounting.
5. Available in the 2400MHz to 2500MHz frequency range.

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, its specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

LFB1X2G45CN3E016



Specifications

Applications	WLAN
Nominal Center Frequency(fo)	2450.00MHz
Bandwidth(BW)	fo±50.00MHz
Insertion Loss in BW I)	1.30dB max. (at 25°C)
Insertion Loss in BW II)	1.60dB max. (-40 to +85°C)
Attenuation(Absolute Value) I)	19.0dB min. at 500.00 to 960.00MHz
Attenuation(Absolute Value) II)	20.0dB min. at 3200.00MHz
Attenuation(Absolute Value) III)	30.0dB min. at 4800.00 to 5000.00MHz
Attenuation(Absolute Value) IV)	30.0dB min. at 7200.00 to 7500.00MHz
VSWR(max.)	2.0
Characteristic Impedance(Nom.)	50Ω
Power Capacity	500mW
Operating Temperature Range	-40°C to 85°C
L x W (size)	1.35x1.05mm
Thickness(max.)	0.8mm

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, its specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.