


Specifications:

规格:

- 1.Voltage rating:250VAC/DC  
额定电压: 250V AC/DC
  - 2.Current rating:5A AC/DC  
额定电流: 5A AC/DC
  - 3.Withstanding voltage:1000V AC/minute  
耐受电压: 1000V AC/分钟
  - 4.Temperature range: -55°C~+105°C  
温度范围: -55°C~+105°C
  - 5.Insulation resistance:500MΩ MIN  
绝缘电阻: 500MΩ MIN
  - 6.Contact resistance:30mΩ Max  
接触电阻: 30mΩ Max
- Material:  
材料:
- 7.Rubber core:PBT+G/F UL94V-0  
胶芯: PBT+C/F UL94V-0
  - 8.The iron shell:Steel ; Tin Plating  
铁壳: 钢 ; 镀锡
  - 9.Terminal:Brass  
端子: 黄铜

X01 XX W X X X X L  
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series NO.
- ② Row No.Pin No.XX-09;15;25;37
- ③ Welding Board Angle :W-Male
- ④ T: Tradutional C: Car-pin
- ⑤ Planting Category: 1:Gold 1u ;2:Gold 2u ;3:Gold 3u ;4:Gold 5u ;5:Gold 15u ;6:Gold 30u ;7:Terminal half- Gold Bright Tin;8: Terminal half- Gold 2u Bright Tin ;9: Terminal half- Gold 3u Bright Tin;10: Terminal half- Gold 5u Bright Tin ;11: Terminal half- Gold 15u Bright Tin;12: Terminal half- Gold 30u Bright Tin ;13: Terminal half- Gold Matte Tin;14:Terminal half- Gold 2u Matte Tin ;15:Terminal half- Gold 3u Matte Tin ;16:Terminal half- Gold 5u Matte Tin ;17:Terminal half- Gold 15u Matte Tin;18:Terminal half- Gold 30u Matte Tin
- ⑥ TinColor:B-BLACK W-White BL-Blue
- ⑦ 1:TYPE-1; 5:TYPE-5
- ⑧ L: Stitching lengthening



| NUMBER OF POSITIONS | DIMENSION |        |        |        |
|---------------------|-----------|--------|--------|--------|
|                     | A±0.25    | B±0.13 | C±0.38 | D±0.25 |
| 9                   | 18.00     | 24.99  | 30.80  | 19.28  |
| 15                  | 26.50     | 33.32  | 39.20  | 27.51  |
| 25                  | 40.00     | 47.04  | 53.05  | 41.28  |
| 37                  | 56.60     | 63.50  | 69.40  | 57.71  |

| MARK      | DESCRIPTION | DATE | REVISED | APPROVED | ANGLAR      | ±5°                    |
|-----------|-------------|------|---------|----------|-------------|------------------------|
| ΔX        |             |      |         |          | L ≤ 4       | ±0.2                   |
| ΔX        |             |      |         |          | 4 < L ≤ 16  | ±0.3                   |
| ΔX        |             |      |         |          | 16 < L ≤ 63 | ±0.4                   |
| MARK      |             |      |         |          | L > 63      | ±0.5                   |
| REVISIONS |             |      |         |          |             | UNSPECIFIED TOLERANCES |



XKB INDUSTRIAL PRECISION CO.,LIMITED

|      |             |                        |
|------|-------------|------------------------|
| DSND | SCALE: N/A  | MODEL TYPE: D-SUB      |
| DWN  | VIEW:       | PART NO.: X01XXWXXXXL  |
| CHKD | UNIT: mm/in | DWG NO.: X-X01XXWXXXXL |
| APPD | SIZE: A4    | WEIGHT SHEET REVISION  |
|      |             | 1/1 A0                 |