
Product datasheet Characteristics

XE2SP2151

limit switch contact block - 1NC+1NO - snap action



Main

Range of product Series name Standard format Product or component type Limit switch contact block Device short name XE2S Associated body ZCKL1 ZCKJ1 ZCKJ1D ZCP21 ZCKS1 ZCKS1 ZCKM1 ZCKM1 ZCKM1 ZCD21 Number of poles 2 Contacts type and composition 1 NO + 1 NC Contacts operation Snap action			
Product or component type Limit switch contact block Device short name XE2S Associated body ZCKL1 ZCKJ1 ZCKJ1D ZCP21 ZCKS1 ZCKS1 ZCKM1 ZCKM1 ZCD21 Number of poles 2 Contacts type and composition Limit switch contact block Image: Contact block Limit switch contact block Limit switch contact block AE2S CKL1 ZCKL1 ZCKJ1 ZCKJ1 ZCKJ1 ZCKS1 ZCKS1 ZCKS1 ZCKM1 ZCD21	Range of product	OsiSense XC	
Device short name XE2S Associated body ZCKL1 ZCKJ1 ZCKJ1D ZCP21 ZCKS1 ZCKS1 ZCKM1 ZCKM1 ZCD21 Number of poles 2 Contacts type and composition 1 NO + 1 NC	Series name	Standard format	
Associated body ZCKJ1 ZCKJ1D ZCP21 ZCKS1 ZCKM1 ZCKM1 ZCD21 Number of poles 2 Contacts type and composition ZCKL1 ZCKJ1D ZCP21 ZCKS1 ZCKS1 ZCKM1 ZCD21	Product or component type	Limit switch contact block	
ZCKJ1 ZCKJ1D ZCP21 ZCKS1 ZCKM1 ZCD21 Number of poles 2 Contacts type and composition 1 NO + 1 NC	Device short name	XE2S	# #
Contacts type and composition 1 NO + 1 NC	Associated body	ZCKJ1 ZCKJ1D ZCP21 ZCKS1 ZCKM1	ino suitability orreliability o
	Number of poles	2	
Contacts operation Snap action	Contacts type and composition	1 NO + 1 NC	
	Contacts operation	Snap action	

Complementary

Product compatibility	XCKM
•	XCKP
	XCR
	XCKL
	XCKS
	XCKD
	XCKJ
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.342 x 1.5 mm²
Contacts insulation form	Zb
Contacts material	Silver plated contacts
Positive opening	With
Minimum actuation speed	0.01 mm/s
Contact code designation	A300, AC-15 (Ue = 240 V, Ie = 3 A) , Ithe = 10 A conforming to EN/IEC 60947-5-1 appendix A Q300, DC-13 (Ue = 250 V, Ie = 0.27 A) conforming to EN/IEC 60947-5-1 appendix A
Resistance across terminals	< 25 mOhm conforming to IEC 60255-7 category 3

[Ui] rated insulation voltage	300 V conforming to CSA C22.2 No 14 500 V degree of pollution 3 conforming to IEC 60947-1 300 V conforming to UL 508
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1
Short circuit protection	10 A by gG cartridge fuse
Electrical durability	5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0843 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months	