## XZCC20FCM30B

female, 1/2 20UNF, 3-pin, elbowed connector - cable gland Pg 7



# Main Accessory / separate part category Accessory / separate part type Electrical connection Collar material Status LED Without Cable connection Cabling accessories Connector Connector Elbowed female connector 1/2 20 UNF, 3 pins Metal Status LED Without Cable connection Screw terminal / wire size <= 0.75 mm² / clamping

capacity 3...6 mm

#### Complementary

| Screw-on     |  |
|--------------|--|
| 250 V AC     |  |
| 4 A          |  |
| Plastic      |  |
| > 1000 GΩ    |  |
| <= 8000 μOhm |  |
| 0.02 kg      |  |
|              | 250 V AC 4 A  Plastic > 1000 GΩ <= 8000 μOhm |

#### Environment

| LIMIOIIIIEIL                          |          |  |
|---------------------------------------|----------|--|
| IP degree of protection               | IP67     |  |
| Ambient air temperature for operation | -4085 °C |  |


### Offer Sustainability

| Sustainable offer status | Not Green Premium product   |
|--------------------------|---|
| RoHS (date code: YYWW)   | Compliant - since 0545 - Schneider Electric declaration of conformity |

# Product data sheet Dimensions Drawings

# XZCC20FCM30B

### **Dimensions**



(1) Cable gland : no. 7 plastic (Pg 7)

# Product data sheet Connections and Schema

# XZCC20FCM30B

### **Connections and Schemes**

