

# GR QSSPA1.23

## OSCONIQ® P 3030

The OSCONIQ P 3030 Colors family LED comes with well known superior robustness, high reliability, long lifetime, low thermal resistance. Compact and proven 3mm x 3mm package and established foot-print. Perfectly addressing applications that demand for high efficiency and long lifetime.



### Applications

- Accent (BAR)
- Architecture
- Stage Lighting (LED & Laser)

### Features:

- Package: SMD epoxy package
- Typ. Radiation: 120°
- Corrosion Robustness Class: 3B
- Lumen maintenance: Test results according to IESNA LM-80 available
- ESD: 8 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)
- Luminous Flux: typ. 73 lm
- Luminous Efficacy: typ. 99 lm/W

---

## Ordering Information

| Type                  | Luminous Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>$\Phi_V$ | Ordering Code |
|-----------------------|-------------------------------------------------------------------|---------------|
| GR QSSPA1.23-KPKR-1-1 | 71.0 ... 89.2 lm                                                  | Q65112A8490   |

---

## Maximum Ratings

| Parameter                                                                | Symbol    |                                    | Values  |
|--------------------------------------------------------------------------|-----------|------------------------------------|---------|
| Operating Temperature                                                    | $T_{op}$  | min.                               | -40 °C  |
|                                                                          |           | max.                               | 125 °C  |
| Storage Temperature                                                      | $T_{stg}$ | min.                               | -40 °C  |
|                                                                          |           | max.                               | 125 °C  |
| Junction Temperature                                                     | $T_j$     | max.                               | 135 °C  |
| Forward current                                                          | $I_F$     | min.                               | 100 mA  |
|                                                                          |           | max.                               | 1000 mA |
| Surge Current<br>$t \leq 10 \mu s$ ; $D = 0.005$ ; $T_j = 25 \text{ °C}$ | $I_{FS}$  | max.                               | 1500 mA |
| Reverse voltage <sup>2)</sup>                                            | $V_R$     | Not designed for reverse operation |         |
| ESD withstand voltage<br>acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)  | $V_{ESD}$ | 8 kV                               |         |

## Characteristics

$I_F = 350 \text{ mA}$ ;  $T_J = 25 \text{ °C}$

| Parameter                                                                                     | Symbol                  |                      | Values                                   |
|-----------------------------------------------------------------------------------------------|-------------------------|----------------------|------------------------------------------|
| Peak Wavelength                                                                               | $\lambda_{\text{peak}}$ | typ.                 | 634 nm                                   |
| Dominant Wavelength <sup>3)</sup><br>$I_F = 350 \text{ mA}$                                   | $\lambda_{\text{dom}}$  | min.<br>typ.<br>max. | 620 nm<br>623 nm<br>632 nm               |
| Spectral Bandwidth at 50% $I_{\text{rel,max}}$                                                | $\Delta\lambda$         | typ.                 | 16 nm                                    |
| Viewing angle at 50% $I_V$                                                                    | $2\phi$                 | typ.                 | 130 °                                    |
| Forward Voltage <sup>4)</sup><br>$I_F = 350 \text{ mA}$                                       | $V_F$                   | min.<br>typ.<br>max. | 1.90 V<br>2.18 V<br>2.50 V               |
| Reverse current <sup>2)</sup>                                                                 | $I_R$                   |                      | Not designed<br>for reverse<br>operation |
| Electrical thermal resistance junction/solderpoint<br>with efficiency $\eta_e = 51 \text{ %}$ | $R_{\text{thJS elec.}}$ | typ.                 | 4.2 K / W                                |

## Brightness Groups

| Group | Luminous Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>min.<br>$\Phi_V$ | Luminous Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>max.<br>$\Phi_V$ |
|-------|---------------------------------------------------------------------------|---------------------------------------------------------------------------|
| KP    | 71.0 lm                                                                   | 76.3 lm                                                                   |
| KQ    | 76.3 lm                                                                   | 82.0 lm                                                                   |
| KR    | 82.0 lm                                                                   | 89.2 lm                                                                   |

## Forward Voltage Groups

| Group | Forward Voltage <sup>4)</sup><br>$I_F = 350 \text{ mA}$<br>min.<br>$V_F$ | Forward Voltage <sup>4)</sup><br>$I_F = 350 \text{ mA}$<br>max.<br>$V_F$ |
|-------|--------------------------------------------------------------------------|--------------------------------------------------------------------------|
| E2    | 1.90 V                                                                   | 2.00 V                                                                   |
| F1    | 2.00 V                                                                   | 2.10 V                                                                   |
| F2    | 2.10 V                                                                   | 2.20 V                                                                   |
| G1    | 2.20 V                                                                   | 2.30 V                                                                   |
| G2    | 2.30 V                                                                   | 2.40 V                                                                   |
| H1    | 2.40 V                                                                   | 2.50 V                                                                   |

Wavelength Groups

| Group | Dominant Wavelength <sup>3)</sup><br>$I_F = 350\text{ mA}$<br>min.<br>$\lambda_{\text{dom}}$ | Dominant Wavelength <sup>3)</sup><br>$I_F = 350\text{ mA}$<br>max.<br>$\lambda_{\text{dom}}$ |
|-------|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| 1     | 620 nm                                                                                       | 632 nm                                                                                       |

---

## Group Name on Label

**Example: KP-1-E2**

Brightness

Wavelength

Forward Voltage

---

KP


1

E2

---


## Relative Spectral Emission <sup>5)</sup>

$I_{\text{rel}} = f(\lambda); I_F = 350 \text{ mA}; T_J = 25 \text{ }^\circ\text{C}$



## Radiation Characteristics <sup>5)</sup>


$I_{\text{rel}} = f(\phi); T_J = 25 \text{ }^\circ\text{C}$






**Forward current** <sup>5)</sup>


$$I_F = f(V_F); T_J = 25\text{ °C}$$

**Relative Luminous Flux** <sup>5), 6)</sup>

$$\Phi_V / \Phi_V(350\text{ mA}) = f(I_F); T_J = 25\text{ °C}$$


**Dominant Wavelength** <sup>5)</sup>

$$\Delta\lambda_{\text{dom}} = f(I_F); T_J = 25\text{ °C}$$




**Forward Voltage** <sup>5)</sup>


$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 350\text{ mA}$$

**Relative Luminous Flux** <sup>5)</sup>

$$\Phi_V / \Phi_V(25^\circ\text{C}) = f(T_j); I_F = 350\text{ mA}$$


**Dominant Wavelength** <sup>5)</sup>

$$\Delta \lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25^\circ\text{C}) = f(T_j); I_F = 350\text{ mA}$$




## Max. Permissible Forward Current

$$I_F = f(T)$$



## Dimensional Drawing <sup>7)</sup>



C67062-A0282-A6..-03

## Further Information


**Approximate Weight:** 24.0 mg

**Package marking:** Anode

**Corrosion test:** Class: 3B  
Test condition: 40°C / 90 % RH / 15 ppm H<sub>2</sub>S / 14 days (stricter than IEC 60068-2-43)

**ESD advice:** The device is protected by ESD device which is connected in parallel to the Chip.

## Recommended Solder Pad <sup>7)</sup>




E067.0346.06 -01

For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning.



Tape and Reel <sup>8)</sup>




Reel Dimensions

| A      | W                   | N <sub>min</sub> | W <sub>1</sub> | W <sub>2 max</sub> | Pieces per PU |
|--------|---------------------|------------------|----------------|--------------------|---------------|
| 180 mm | 12 + 0.3 / - 0.1 mm | 60 mm            | 12.4 + 2 mm    | 18.4 mm            | 600           |

## Barcode-Product-Label (BPL)

|                                                                                    |                |                                                                                                             |                                                                                     |
|------------------------------------------------------------------------------------|----------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>OSRAM Opto Semiconductors</b>                                                   |                | LX XXXX                                                                                                     | BIN1: XX-XX-X-XXX-X                                                                 |
| (6P) BATCH NO: 1234567890                                                          |                | RoHS Compliant                                                                                              |                                                                                     |
|   |                |  ML Temp ST<br>X XXX °C X |  |
| (1T) LOT NO: 1234567890                                                            | (9D) D/C: 1234 |                                                                                                             |                                                                                     |
|   |                | Pack: RXX<br>DEMY XXX<br>X_X123_1234.1234 X                                                                 |                                                                                     |
| (X) PROD NO: 123456789(Q)QTY: 9999                                                 |                | (G) GROUP: XX-XX-X-X                                                                                        |                                                                                     |
|  |                |                                                                                                             |                                                                                     |

OHA04563


Dry Packing Process and Materials <sup>7)</sup>

OHA00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.



Schematic Transportation Box <sup>7)</sup>



Dimensions of Transportation Box

| Width      | Length     | Height    |
|------------|------------|-----------|
| 195 ± 5 mm | 195 ± 5 mm | 30 ± 5 mm |

## Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet falls into the class **exempt group (exposure time 10000 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

This device is designed for specific/recommended applications only. Please consult OSRAM Opto Semiconductors Sales Staff in advance for detailed information on other non-recommended applications (e.g. automotive).

Change management for this component is aligned with the requirements of the lighting market.

For further application related information please visit [www.osram-os.com/appnotes](http://www.osram-os.com/appnotes)

## Disclaimer

### Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on the OSRAM OS website.

### Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

### Product and functional safety devices/applications or medical devices/applications

OSRAM OS components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

OSRAM OS products are not qualified at module and system level for such application.

In case Buyer – or Customer supplied by Buyer – considers using OSRAM OS components in product safety devices/applications or medical devices/applications, Buyer and/or Customer has to inform the local sales Partner of OSRAM OS immediately and OSRAM OS and Buyer and /or Customer will analyze and coordinate the customer-specific request between OSRAM OS and Buyer and/or Customer.

---

## Glossary

- 1) **Brightness:** Brightness values are measured during a current pulse of typically 10 ms, with a tolerance of  $\pm 7\%$ .
- 2) **Reverse Operation:** Not designed for reverse operation. Continuous reverse operation can cause migration and damage of the device.
- 3) **Wavelength:** The wavelength is measured at a current pulse of typically 10 ms, with a tolerance of  $\pm 0.5$  nm.
- 4) **Forward Voltage:** The Forward voltage is measured during a current pulse duration of typically 1 ms with a tolerance of  $\pm 0.05$  V.
- 5) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 6) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 7) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with  $\pm 0.1$  and dimensions are specified in mm.
- 8) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

---

## Revision History

| Version | Date       | Change          |
|---------|------------|-----------------|
| 1.0     | 2019-04-22 | Initial Version |

---

**Published by OSRAM Opto Semiconductors GmbH** EU RoHS and China RoHS compliant product  
**Leibnizstraße 4, D-93055 Regensburg**  
**www.osram-os.com © All Rights Reserved.**



此产品符合欧盟 RoHS 指令的要求；  
按照中国的相关法规和标准，不含有毒有害物质或元素。