



Part Number : 1200980203

Product Description : PROFIBUS 90° Female/Male D-Sub Connector to Pigtail, With Programming Port, 22 AWG, PUR Cable, 1.0m (3.28') Length

Series Number : 120098

Status : Active

Product Category : Circular Industrial Cordsets

Engineering Number : P03S07PP4M010

Documents & Resources

Drawings

Drawing 1200980203_sd.pdf

Product Environment Compliance

Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
--------	--------

Category	Circular Industrial Cordsets
Series	120098
Description	PROFIBUS 90° Female/Male D-Sub Connector to Pigtail, With Programming Port, 22 AWG, PUR Cable, 1.0m (3.28') Length
Comments	With Programming Port
IP Rating	IP67
Product Family	PROFIBUS Solutions
Product Name	PROFIBUS
Protocol	N/A
Region	America, Asia, Europe
Type	Single Ended
UPC	78172504509

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Cable Diameter	8.00mm (.315")
Cable Length	1.0m (3.28')
Color - Cable Jacket	Violet
Connector End A	D-Sub (9-pin)
Connector End B	Pigtail
Coupling Style	Threaded
Gender	Female/Male to Pigtail
Keyway	None
LED Indicator	No
Material - Cable Jacket	PUR
Material - Connector Body	PUR
Material - Contact	N/A
Material - Coupling Nut	Gray Anodized Aluminum
Material - Plating Mating	N/A
Orientation	90°/90° to Pigtail
Poles	N/A

Temperature Range - Operating	0° to +60°C
Wire/Cable Type	Shielded-Twisted Pair
Wire Size (AWG)	22

This document was generated on Sep 16, 2024