

规格说明: Specifications:  
电气特性: Electrical:

1. 额定电流: Current Rating  
1A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage  
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance  
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force  
Mate force: 35N (MAX)  
Unmate force: 7N (MIN)

材料: Material:

1. 塑胶: Housing:  
PBT
2. 端子: Contact:  
Copper Alloy C2680
3. 外壳: Shell:  
SPCC

电镀Finish:

1. 端子: Contact:  
Plated Gold in Mating Area,  
Tin On Solder Tails
2. 外壳: Shell  
Nickel Plating

温度范围: Temperature Range:  
-30°C to +80°C

TOLERANCE UNLESS OTHERWISE SPECIFIED  
.XXX ±0.10  
.XX ±0.20  
.X ±0.30  
.X\* ±3°

产品名称  
PART NAME:

USB BF90度

料号

HX TYPE-BF 90

REV:

DESCRIPTION

REV BY

APPROVED

DATE

MATL:


SEE SPECIFICATION

APPROVED

罗小春

A

PROJECTION:



THIRD ANGLE PROJECTION

CHECKED

张伟

UNIT:

SCALE

REV (NO)

SHEET

DRAWN

黄彬

mm

1:1

A

1 OF 1

DATE

2020. 6. 10



深圳市韩下电子有限公司