





RECOMMENDED STRAIN RELIEF ATTACHMENT

SINGLE STAY CORD

TIE OVERHAND KNOT ON STAY CORD 1" FROM END OF JACKET (NF-14/U) AND ASSEMBLE AS SHOWN



DUAL STAY CORD

TIE CORDS AROUND STRAIN RELIEF ANCHOR WITH SQUARE KNOT AND APPLY VARNISH TO KNOT

SECTION B-B

NOTES:

1. TELEPHONE PLUG MATES WITH U-92-A TELEPHONE JACK & NEXUS TELEPHONE JACKS SERIES TJ-120.
2. TERMINALS 1 & 3 ARE FOR MICROPHONE CIRCUITS. TERMINALS 2 & 4 ARE FOR EARPHONE CIRCUITS.
3. THIS PLUG MEETS WITH THE REQUIREMENTS OF MIL-STD-177 & U.S. AIR FORCE DRAWING 53C13465

REV.	REVISION	DATE	BY
C	2) SECT B-B REVISED	1/1/70	
	1) SECT B-B WAS SECT A-A		

REV.	REVISION	DATE	BY
B	1) GRADE G WAS TYPE III	7/7/67	
	2) ADDED SECTION A-A		
	3) ADDED TP-102-13		
	4) TP-102-20 WAS TP-102-14		
	5) TP-102-13 WAS TP-102-3		
	6) TP-102-16 WAS TP-102-8		
	7) TP-102-18 WAS TP-102-15		

DES. BY M. Ambro	DATE 12-3-66	MATERIAL AS SPECIFIED
CHECKED BY EOT	DATE 12-4-66	FINISH AS SPECIFIED
APPROVED BY		WEIGHT
		SCALE 2:1
		TITLE TELEPHONE PLUG U-93A/U
		DO NOT SCALE DIMS.
		SHEET OF
		NEXUS STAMFORD, CONN.
		C TP-102

201-102

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[TP-102](#)

[U-93A/U](#)