

| REVISIONS |         |          |                 |           |        |
|-----------|---------|----------|-----------------|-----------|--------|
| REV.      | ECN NO. | LOCATION | DESCRIPTION     | DATE      | DESIGN |
| A0        | N/A     |          | INITIAL RELEASE | /         | /      |
| A1        | N/A     |          | 图面升级整理图面        | 2024.9.24 | 阿树     |

■SPECIFICATIONS

- Voltage rating:250V AC/DC
- Current rating:2A AC/DC
- Withstanding Voltage:1000V AC/minute
- Temperature range:-40°C~+125°C
- Insulation resistance:≥1000MΩ
- Contact resistance:≤20mΩ

PART NO.:

X2011 W R-XX A R-P SN  
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ①Series No  
②Category:W-Wafer  
③Welding Board Angle:R-Stright 90°  
④Row No.Pin No:XX-02~16Pin  
⑤Plug the Pin&Special NO:  
A-With Baffle  
⑥Special NO: R-DIP 2.2mm  
⑦Material:LP-LCP UL94V-0 ,Natural  
⑧Planting: SN-Bright tin plating

| Poles | Dimensions (mm) |       |       | Poles | Dimensions (mm) |       |       |
|-------|-----------------|-------|-------|-------|-----------------|-------|-------|
|       | A               | B     | C     |       | A               | B     | C     |
| 02    | 2.00            | 4.90  | 6.00  | 10    | 18.00           | 20.90 | 22.00 |
| 03    | 4.00            | 6.90  | 8.00  | 11    | 20.00           | 22.90 | 24.00 |
| 04    | 6.00            | 8.90  | 10.00 | 12    | 22.00           | 24.90 | 26.00 |
| 05    | 8.00            | 10.90 | 12.00 | 13    | 24.00           | 26.90 | 28.00 |
| 06    | 10.00           | 12.90 | 14.00 | 14    | 26.00           | 28.90 | 30.00 |
| 07    | 12.00           | 14.90 | 16.00 | 15    | 28.00           | 30.90 | 32.00 |
| 08    | 14.00           | 16.90 | 18.00 | 16    | 30.00           | 32.90 | 34.00 |
| 09    | 16.00           | 18.90 | 20.00 |       |                 |       |       |

|                   |          |               |                      |
|-------------------|----------|---------------|----------------------|
| X2011WR-XXAR-LPSN | LCP      | Brass         | X2011H-A             |
| PART NO           | Material | Material(Pin) | Suitable XKB Housing |

|                        |       |
|------------------------|-------|
| AuGLAR                 | ±5°   |
| X.                     | ±0.40 |
| X.x                    | ±0.30 |
| X.xx                   | ±0.20 |
| X.xxx                  | ±0.15 |
| UNSPECIFIED TOLERANCES |       |



|          |    |       |       |             |                              |
|----------|----|-------|-------|-------------|------------------------------|
| DESIGN   | 阿树 | VIEW: |       | MODEL TYPE: | 2.00mm Crimp Style Connector |
| CHECKED  |    | UNIT: | mm/in | PART NO.:   | X2011WR-XXAR-LPSN            |
| APPROVED |    | SIZE: | A4    | DWG NO.:    |                              |

XKB INDUSTRIAL PRECISION CO.,LIMITED

|       |      |          |
|-------|------|----------|
| SCALE | PAGE | REVISION |
| N/A   | 1/1  | A1       |

