

Sep.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.

APPLICABLE STANDARD					
Operating condition	Operating temperature range	-30 to +85 [degree C] (20 to 80%RH)	Storage temperature range	-10 to +60 [degree C] (40 to 70%RH)	
	Characteristic impedance		Applicable cable		
	Applicable Connector				
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
Dimension, Construction and Finishing	Shall be carried out visually and measuring instrument.		According to drawing	X	X
Marking	Confirmed visually			X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
	0				
REMARK			APPROVED	MT. SHIBUTANI	12. 01. 19
			CHECKED	SJ. SUZUKI	12. 01. 18
			DESIGNED	YA. SANO	12. 01. 18
			DRAWN	YA. SANO	12. 01. 18
Note QT:Qualification Test, AT:Assurance Test			DRAWING NO.	ELC4-177879-00	
HRS	SPECIFICATION SHEET		PART NO.	BF4-T2	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL831-0006-0-00	 1/1