



Main

Range	Linergy
Product name	HK
Product or Component Type	Plug outlet
Poles description	2P
[lth] conventional free air thermal current	32 A
I ² t on activation	200000 A ² .s
Number of points	1
Number of cables	2 0.006 in ² (4 mm ²)
Cable length	3.3 ft (1 m)
Quantity per Set	Set of 6

Complementary

[Ui] rated insulation voltage	600 V CSA 600 V UL 690 V IEC 60439-1
Peak current	25 kA
Width	0.7 in (18 mm)
Height	1.8 in (46 mm)
Depth	1.5 in (38 mm)
Net Weight	0.09 lb(US) (0.04 kg)

Environment

Standards	IEC 60439
Product Certifications	UL[RETURN]DNV[RETURN]LROS (Lloyds register of shipping)[RETURN]CSA

Ordering and shipping details

Category	US10I1122623
Discount Schedule	0I11
GTIN	3389110588996
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.4 in (8.6 cm)
Package 1 Width	8.7 in (22.2 cm)
Package 1 Length	9.06 in (23 cm)
Package 1 Weight	4.2 oz (119 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	3.4 in (8.6 cm)
Package 2 Width	8.7 in (22.2 cm)
Package 2 Length	9.06 in (23 cm)
Package 2 Weight	25.3 oz (718 g)

Unit Type of Package 3	S04
Number of Units in Package 3	54
Package 3 Height	11.8 in (30 cm)
Package 3 Width	15.7 in (40 cm)
Package 3 Length	23.6 in (60 cm)
Package 3 Weight	17.293 lb(US) (7.844 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------