



RF Products

RF Connectors

Product Groups

Tools

[Crimp tools](#)
[Inserts](#)
[Spanners](#)
[Stripping tool](#)
[Table press](#)
[Tap drills](#)

Torque wrenches

[Accessories](#)

[Knowledge base](#)

RF Cables

RF Cable Assemblies

Wireless Data Links

Antennas

Lightning Protectors

Power Splitters

RF Components

RF general info

Fiber Optic products

Wire + Cable products

Product search

Torque wrenches



Standard style

- high accuracy
- ergonomic style
- easy handling

Coupling nuts and fastening nuts have to perform reliably within a connection. In order to meet this requirement, tightening with a specific torque is recommended.

Standard style torque spanners as well as box spanners for applications with high packing densities are available.



H+S Type	Item no.	for Series	Torque	Opening
74_Z-0-0-21	22543130	SMA / PC 3.5	1.00 Nm	8.0 mm / .315 in.
74_Z-0-0-45	22544232	SMC	0.35 Nm	6.0 mm / .236 in.
74_Z-0-0-79	22642374	SMA economic	0.45 Nm	8.0 mm / .315 in.
74_Z-0-0-80	22544821	SMA hermetic	1.95 Nm	7.0 mm / .276 in.
74_Z-0-0-174	22643898	SK	1.30 Nm	8.0 mm / .315 in.
74_Z-0-0-189	22644368	SK hermetic	2.00 Nm	8.0 mm / .315 in.
74_Z-0-0-192	22645084	TNC	1.00 Nm	15.0 mm / .591 in.
74_Z-0-0-193	22645085	N	1.00 Nm	20.0 mm / .787 in.
74_Z-0-0-321	22651994	N	1.00 Nm	19.0 mm / .748 in.
74_Z-0-0-330	22658130	N	1.00 Nm	18.0 mm / .709 in.
74_Z-0-0-373	23021864	TNC	1.00 Nm	14.0 mm / .551 in.

Box spanner style

H+S Type	Item no.	for Series	Torque	Opening
74_Z-0-0-77	22544820	SMA	1.00 Nm	8.0 mm / .315 in.
74_Z-0-0-78	22641379	SMA economic	0.45 Nm	8.0 mm / .315 in.



Product finder

TYPE ITEM NUMBER



RF product search

74_Z-	22644235	SMC	0.35	6.0
0-0-			Nm	mm /.236
147				<i>in.</i>
74_Z-	22645579	BMA	2.00	8.0
0-0-		hermetic	Nm	mm /.315
214				<i>in.</i>

.....
[privacy policy](#) | [disclaimer](#) © 2004 HUBER+SUHNER