



Representative Image

Catalog No. 5254

Description: 1 INCH NON-INSUL 90 DEG LT CONN

UPC No 786210052540

Home > Cable Protection Systems > T&B Liquidtight Fittings > Liquid tight connectors

Liquidtight Conduit Fitting, 90 Degree 1 Inch, Non-Insulated Malleable Iron

Descriptors

Category	Liquid tight connectors
Type	Connectors-90 Degree
Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

Specifications

Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

Classifications

Brand Name	T&B Liquidtight Fittings
Standard	UL E23018, CSA

Dimensions

Size	1 Inch
------	--------

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH SVHC	REACH 223 Compliant
TSCA	TSCA Section 6(h) Compliant

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT

ETIM	EC001180 Screw connection for protective metallic hose
Thread connection size	Other
One-piece	N
Material housing	Other
Surface protection	Other
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y