



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 100V AC, DC
- 3、Temperatuer Range: -25°C~ +85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: PA66 UL94-V0

Circuit	Part NO.	Dimensions mm	
		A	B
2	HC-PA-2Y	2.00	6.00
3	HC-PA-3Y	4.00	8.00
4	HC-PA-4Y	6.00	10.00
5	HC-PA-5Y	8.00	12.00
6	HC-PA-6Y	10.00	14.00
7	HC-PA-7Y	12.00	16.00
8	HC-PA-8Y	14.00	18.00
9	HC-PA-9Y	16.00	20.00
10	HC-PA-10Y	18.00	22.00
11	HC-PA-11Y	20.00	24.00
12	HC-PA-12Y	22.00	26.00
13	HC-PA-13Y	24.00	28.00
14	HC-PA-14Y	26.00	30.00
15	HC-PA-15Y	28.00	32.00
16	HC-PA-16Y	30.00	34.00

			GENEAL TOLERANCE		制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM	TOL	审 核 CHECK					
			X.X	±0.30	批 准 APPROVAL		产品名称 TITLE	PA (2.0)孔座	版本 REV.	A
1			初版发行		比 例 SCALE		产品料号 PART NO.	HC-PA-NY	单 位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°	投 影 Projection		材 料 MATERIAL		页 次 SHEET	1/1