


REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A	①X2	产品外观及尺寸变更，图面升级整理图面	2025.05.23	阿树






- SPECIFICATIONS
- Applicable Wire:AWG.#28~#32
 - Voltage rating:125V AC/DC
 - Current rating:1A AC/DC
 - Withstanding Voltage:250V AC/minute
 - Temperature range:-45°C+105°C
 - Insulation resistance:≥100MΩ
 - Contact resistance:≤20mΩ


PART NO.:

X9821 W V S-XX-9T SN
① ② ③ ④ ⑤ ⑥ ⑦

- ①Series No
②Category:W-Wafer
③Welding Board Angle:V-Straight 180°
④Welding Way: S-SMT
⑤Row No.Pin No:XX-02~16Pin
⑥Material:9T-PA9T UL94V-0
⑦Planting: SN-Bright Tin Plating



2P,3P产品为一个开口
3P产品以上为两个开口



Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
02	4.25	1.25	7.30	10	14.25	11.25	17.30
03	5.50	2.50	8.50	11	15.50	12.50	18.50
04	6.75	3.75	9.80	12	16.75	13.75	19.80
05	8.00	5.00	11.00	13	18.00	15.00	21.00
06	9.25	6.25	12.30	14	19.25	16.25	22.30
07	10.50	7.50	13.50	15	20.50	17.50	23.50
08	11.75	8.75	14.80	16	21.75	18.75	24.80
09	13.00	10.00	16.00				

X9821WVS-XX-9TSN	PA9T UL 94V-0	Brass	Tin-Plated	X9821H
PART NO	Material	Material(pin)	Finish(pin)	Suitable XKB Terminal

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:	①	MODEL TYPE:	1.25mm Crimp Style Connectors
CHECKED		UNIT:	mm/in	PART NO.:	X9821WVS-XX-9TSN
APPROVED		SIZE:	A4	DWG NO.:	