

Actuator

46-
2134.3120.000

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/46-2134.3120.000>

Your product:



46-2134.3120.000 Actuator

FRONT

Front bezel material:	Metal
Front bezel colour:	Silver
Front dimension:	Ø 29,5 mm
Front form:	round

MOUNTING

Design:	raised
Mounting cut-out:	Ø 22.3 mm

OPERATING-/INDICATION PART

Lens material:	Plastic
Lens shape:	flush
Lens optics:	opaque
Lens colour:	Red
Lens illumination:	non illuminative

ELECTRICAL CHARACTERISTICS

Protection class:	II
--------------------------	----

MECHANICAL CHARACTERISTIC

Tightening torque:	2 ... 3 Nm (17.7 ... 26.6 Lb-in)
Mechanical lifetime:	500 000 cycles of operation

Weight: 0.033 kg
Switching action: Maintained

AMBIENT CONDITION

Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)
Operating temperature: - 25 °C ... + 55 °C
IK front protection: IK03
IP front protection: IP65
Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Shock resistance: 50g, 11ms (EN-IEC 60068-2-27)

CERTIFICATE

Conformities: CE
Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

OTHER

Short Description: Actuator, Ø 22.3 mm, Ø 29,5 mm, flush, non illuminative, Red, Plastic, opaque, round, Silver, Metal, Maintained, IP65, IK03

max. number of switching elements: 6

Housing colour: Black

Housing material: Plastic

Dimension drawings:

