



Circuit Diagram

P C B Layout(Top view)

Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:—20℃~70℃
 Operating force:3—20N
 Operating Life:5,000cycles

| | | | | | | |
|---------|------|-------|--------------|---------|--------|--------|
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
| | A | | NEW | | | |

| | | | | | | |
|----------------|----------------|---------------------|------------|---------------------|--------------|--------------|
| ② | Shunt terminal | | 5 | Phosphor bronze | Plating Au | |
| ① | Housing | | 1 | PPA | Black | |
| ITEM | PART NAME | Serial number | QTY. | MATERIAL | FINISHING | REMARK |
| APPROVALS | | DATE | | | | |
| DRAWN | | xu qi feng | 2014.11.28 | ELECTRONICS CO.,LTD | | |
| CHECKED | | | TITLE: | | PHONE JACKES | |
| APPROVALS | | | PART NO. | | PJ-610 | |
| TOLERANCES ARE | | 30 ^{±0.15} | ±0.30 | ANGLE | SCALE: 1:1 | PROJ. |
| | | 10 ^{±0.20} | ±0.20 | UNIT: mm | | |
| | | 5 ^{±0.10} | ±0.15 | ±2' | DRAWING NO. | SHEET 1 OF 1 |
| | | ~ 5 | ±0.10 | | | |

