



PINNO.	CONNECTOR TERMINAL
P1	VCC:PWRSIGNALANDGND
P2	RST: RESET SIGNAL
P3	CLK:CLOCKINGSIGNAL
P4	GND:RWR SIGNALANDGND
P5	VPP: PROGRAMMING VOLTAGE
P6	I0:SERIALDATAINPUTOUTPUT

Note:

- 1.Electrical performance:  
voltage rating: 12V DC  
contact resistance:100mΩ max  
dielectric strength: 500V AC  
for 1 minrte.
- 2.Mechanical performance:  
insertion force: 0.5kgf~1.5kgf  
ejection force: 0.5kgf~1.5kgf  
cycle life: 2000 times.
- 3.Packaging: 600pcs/Reel

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑥	Sliding Block	---	1	LCP	Black	---
⑤	Clasp	---	1	SUS	Ni Plated	---
④	Spring	---	1	SUS	Ni Plated	---
③	Shell	---	1	SUS	Ni Plated	---
②	Terminal	---	6	Phosphor Bronze	Sn Plated	---
①	Housing	---	1	LCP	Black	---

APPROVALS	DATE	TITLE:
DRAWN JKUN.LU	2014/9/29	ELECTRONICS CO.,LTD
CHECKED		SIM

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	SHEET
	A		NEW				30~φ以上 ±0.30	±2°	mm	1:1	1 OF 1
			△20180409 上盖外观变更				10~30 ±0.25				
							5~10 ±0.20				
							~5 ±0.15				