

NCE N-Channel Enhancement Mode Power MOSFET

Description


The NCE0106R uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

General Features

- $V_{DS} = 100V, I_D = 6A$
 $R_{DS(ON)} < 140m\Omega @ V_{GS}=10V$ (Typ:110m Ω)
- High density cell design for ultra low R_{dson}
- Fully characterized avalanche voltage and current
- Excellent package for good heat dissipation
- **Pb free terminal plating**
- **RoHS compliant**
- **Halogen free**

Application

- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply



Schematic diagram



SOT-223 top view

Package Marking and Ordering Information

| Device Marking | Device | Device Package | Reel Size | Tape width | Quantity |
|----------------|----------|----------------|-----------|------------|------------|
| NCE0106R | NCE0106R | SOT-223-3L | Ø330mm | 12mm | 2500 units |

Absolute Maximum Ratings ($T_A=25^\circ C$ unless otherwise noted)

| Parameter | Symbol | Limit | Unit |
|--|--------------------|------------|------------|
| Drain-Source Voltage | V_{DS} | 100 | V |
| Gate-Source Voltage | V_{GS} | ± 20 | V |
| Drain Current-Continuous | I_D | 6 | A |
| Drain Current-Continuous($T_C=100^\circ C$) | $I_D(100^\circ C)$ | 4.2 | A |
| Drain Current-Pulsed ^(Note 1) | I_{DM} | 24 | A |
| Maximum Power Dissipation | P_D | 3 | W |
| Operating Junction and Storage Temperature Range | T_J, T_{STG} | -55 To 150 | $^\circ C$ |

Thermal Characteristic

| | | | |
|---|-----------------|------|--------------|
| Thermal Resistance,Junction-to-Ambient ^(Note 2) | $R_{\theta JA}$ | 71 | $^\circ C/W$ |
| Thermal Resistance,Junction-to-Case ^(Note 2) (Drain) | $R_{\theta JC}$ | 41.7 | $^\circ C/W$ |

Electrical Characteristics ($T_A=25^\circ C$ unless otherwise noted)

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|--------------------------------|------------|--------------------------|-----|-----|-----|------|
| Off Characteristics | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V I_D=250\mu A$ | 100 | 110 | - | V |


| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|---|--------------|---|-----|------|-----------|------------|
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS}=100V, V_{GS}=0V$ | - | - | 1 | μA |
| Gate-Body Leakage Current | I_{GSS} | $V_{GS}=\pm 20V, V_{DS}=0V$ | - | - | ± 100 | nA |
| On Characteristics (Note 3) | | | | | | |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}=V_{GS}, I_D=250\mu A$ | 1.2 | 1.8 | 2.5 | V |
| Drain-Source On-State Resistance | $R_{DS(ON)}$ | $V_{GS}=10V, I_D=5A$ | - | 110 | 140 | m Ω |
| Forward Transconductance | g_{FS} | $V_{DS}=5V, I_D=5A$ | - | 8 | - | S |
| Dynamic Characteristics (Note 4) | | | | | | |
| Input Capacitance | C_{iss} | $V_{DS}=25V, V_{GS}=0V,$ $F=1.0MHz$ | - | 690 | - | PF |
| Output Capacitance | C_{oss} | | - | 120 | - | PF |
| Reverse Transfer Capacitance | C_{rss} | | - | 90 | - | PF |
| Switching Characteristics (Note 4) | | | | | | |
| Turn-on Delay Time | $t_{d(on)}$ | $V_{DD}=50V, R_L=15\Omega$ $V_{GS}=10V, R_G=2.5\Omega$ | - | 11 | - | nS |
| Turn-on Rise Time | t_r | | - | 7.4 | - | nS |
| Turn-Off Delay Time | $t_{d(off)}$ | | - | 35 | - | nS |
| Turn-Off Fall Time | t_f | | - | 9.1 | - | nS |
| Total Gate Charge | Q_g | $V_{DS}=50V, I_D=5A,$ $V_{GS}=10V$ | - | 15.5 | - | nC |
| Gate-Source Charge | Q_{gs} | | - | 3.2 | - | nC |
| Gate-Drain Charge | Q_{gd} | | - | 4.7 | - | nC |
| Drain-Source Diode Characteristics | | | | | | |
| Diode Forward Voltage (Note 3) | V_{SD} | $V_{GS}=0V, I_S=6A$ | - | - | 1.2 | V |
| Diode Forward Current (Note 2) | I_S | | - | - | 6 | A |

Notes:


1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, $t \leq 10$ sec.
3. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
4. Guaranteed by design, not subject to product

Test Circuit


1) E_{AS} test circuit



2) Gate charge test circuit



3) Switch Time Test Circuit



Typical Electrical and Thermal Characteristics (curves)

Figure1. Source-Drain Diode Forward Voltage




Figure2. Safe operating area




Figure3. Output characteristics




Figure4. Transfer characteristics




Figure5. Static drain-source on resistance




Figure6. $R_{DS(ON)}$ vs Junction Temperature




Figure7. BV_{DSS} vs Junction Temperature




Figure8. $V_{GS(th)}$ vs Junction Temperature




Figure9. Gate charge waveforms




Figure10. Capacitance





Figure11. Normalized Maximum Transient Thermal Impedance






Figure12. I_D vs Junction Temperature

SOT-223 Package Information



NOTES:
DO NOT INCLUDE MOLD FLASH
OR PROTRUSIONS

| SYMBOL | MIN | NOM | MAX |
|------------|----------|------|------|
| A | 1.55 | — | 1.80 |
| A1 | 0.02 | — | 0.12 |
| A2 | 1.45 | 1.60 | 1.75 |
| A3 | 0.60 | 0.70 | 0.80 |
| b | 0.60 | — | 0.80 |
| b1 | 2.90 | — | 3.10 |
| c | 0.24 | — | 0.32 |
| D | 6.20 | 6.30 | 6.50 |
| E | 6.70 | 7.00 | 7.30 |
| E1 | 3.30 | 3.50 | 3.70 |
| e | 2.299REF | | |
| e1 | 4.598REF | | |
| L | 0.90MIN | | |
| L2 | 0.30BSC | | |
| θ | 0° | — | 10° |
| θ_1 | 10° | 12° | 14° |
| θ_2 | 10° | 12° | 14° |



Attention:

- Any and all NCE power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your NCE power representative nearest you before using any NCE power products described or contained herein in such applications.
- NCE power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all NCE power products described or contained herein.
- Specifications of any and all NCE power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- NCE power Semiconductor CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all NCE power products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of NCE power Semiconductor CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. NCE power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the NCE power product that you intend to use.
- This catalog provides information as of Sep.2010. Specifications and information herein are subject to change without notice.