



P . C . B LAYOUT

Specifications:

规格:

Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage:500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range:-40°C-+105°C
 温度范围: -40°C-+105°C
 Insulation resistance: 1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance:20mΩ Max
 接触电阻: 20mΩ Max

X2001 W V - 2xXX B - 6T V01
 ① ② ③ ④ ⑤ ⑥ ⑦

- 1.Series No
- 2.Category:W-Wafer
- 3.Welding Board Angle:V-Stright 180°
- 4.Row No.Pin No :2xXX-2x03-2x32P
- 5.Category:B-have gaps
- 6.Material:6T-Nylon 6T UL94V-0
- 7.Plating:V01-Gold Flash

| Poles | Dimensions | | Poles | Dimensions | |
|-------|------------|-------|-------|------------|-------|
| | A | B | | A | B |
| 2x03 | 4.00 | 13.30 | 2x13 | 24.00 | 33.30 |
| 2x04 | 6.00 | 15.30 | 2x15 | 28.00 | 37.30 |
| 2x05 | 8.00 | 17.30 | 2x17 | 32.00 | 41.30 |
| 2x06 | 10.00 | 19.30 | 2x20 | 38.00 | 47.30 |
| 2x07 | 12.00 | 21.30 | 2x22 | 42.00 | 51.30 |
| 2x08 | 14.00 | 23.30 | 2x25 | 48.00 | 57.30 |
| 2x09 | 16.00 | 25.30 | 2x30 | 58.00 | 67.30 |
| 2x10 | 18.00 | 27.30 | 2x32 | 62.00 | 71.30 |
| 2x12 | 20.00 | 31.30 | / | | |

| | | | |
|---------------------|----------|---------------|--------------------|
| X2001WV-2xXXB-6TV01 | Nylon 6T | Brass | X2001H3 / X2001HA3 |
| PART NO | Material | Material(Pin) | Suitable XKB IDC |

| | | |
|------|-------------|--|
| DSND | SCALE: N/A | MODEL TYPE: 2.0mm Crimp Style Connector |
| DWN | VIEW: | PART NO.: X2001WV-2xXXB-6TV01 |
| CHKD | UNIT: mm/in | DWG NO.: X-X2001WV-2xXXB-6TV01 |
| APPD | SIZE: A4 | |



XKB INDUSTRIAL PRECISION CO., LIMITED

| | | |
|--------|-------|----------|
| WEIGHT | SHEET | REVISION |
| | 1/1 | A0 |

广东星坤科技股份有限公司

| | |
|------|-------------|
| Δx | 日期 |
| Δx | |
| Δx | |
| MARK | DESCRIPTION |

文件工程章

| REVISIONS | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|-----------|------|---------|----------|------------------------|
| | | | | |
| | | | | |
| | | | | |
| | | | | |