




RoHS

版本 REV A0	变更事项 CHANGE CONTENT	依据 THEREUNDER	变更日期 DATE
-----------------	------------------------	------------------	--------------



技术要求:

Technical requirement

一. 电气性能:

electrical performance

1-1. 额定电流: 1A AC DC.

rated current: 1A AC DC.

1-2. 接触电阻: ≤20mΩ

Contact resistance: ≤20mΩ

1-3. 绝缘电阻: ≥1000MΩ

Insulation resistance: ≥1000MΩ

1-4. 耐压: 550V AC/Minute

withstand voltage: 550V AC/Minute

二. 物理特性:

Physical characteristics

2-1. 环境温度: -25℃~105℃

environmental temperature: -25℃~105℃

2-2. 焊接温度: +260℃, 10s max

welding temperature: +260℃, 10s max

三. 材质:


Material

3-1. 塑胶: PA6T(Black) UL94V-0

plastic: PA6T(Black) UL94V-0

3-2. 插针: 磷铜/镀金

pin: Phosphor/Gold plated



P.C.B LAYOUT

PIN	A	B	C
2x2A	2.94	1.27	/
2x3A	4.21	2.54	1.27
2x4A	5.48	3.81	2.54
2x5A	6.75	5.08	3.81
2x6A	8.02	6.35	5.08
2x7A	9.29	7.62	6.35
2x8A	10.56	8.89	7.62
2x9A	11.83	10.16	8.89
2x10A	13.10	11.43	10.16
2x11A	14.37	12.70	11.43
2x12A	15.64	13.97	12.70
2x13A	16.91	15.24	13.97
2x14A	18.18	16.51	15.24
2x15A	19.45	17.78	16.51
2x16A	20.72	19.05	17.78
2x17A	21.99	20.32	19.05
2x18A	23.26	21.59	20.32
2x19A	24.53	22.86	21.59
2x20A	25.80	24.13	22.86
2x21A	27.07	25.40	24.13
2x22A	28.34	26.67	25.40
2x23A	29.61	27.94	26.67
2x24A	30.88	29.21	27.94
2x25A	32.15	30.48	29.21
2x26A	33.42	31.75	30.48
2x27A	34.69	33.02	31.75
2x28A	35.96	34.29	33.02
2x29A	37.23	35.56	34.29
2x30A	38.50	36.83	35.56
2x31A	39.77	38.10	36.83
2x32A	41.04	39.37	38.10
2x33A	42.31	40.64	39.37
2x34A	43.58	41.91	40.64
2x35A	44.85	43.18	41.91
2x36A	46.12	44.45	43.18
2x37A	47.39	45.72	44.45
2x38A	48.66	46.99	45.72
2x39A	49.93	48.26	46.99
2x40A	51.20	49.53	48.26
2x41A	52.47	50.80	49.53
2x42A	53.74	52.07	50.80
2x43A	55.01	53.34	52.07
2x44A	56.28	54.61	53.34
2x45A	57.55	55.88	54.61
2x46A	58.82	57.15	55.88
2x47A	60.09	58.42	57.15
2x48A	61.36	59.69	58.42
2x49A	62.63	60.96	59.69
2x50A	63.90	62.23	60.96

3	包装	<input type="checkbox"/> 袋装 <input checked="" type="checkbox"/> 管装 <input type="checkbox"/> 卷装 <input type="checkbox"/> 盒装	1	PCS
2	塑胶	PH1.27*2.0 2*nP PA6T料	1	PCS
1	端子	SMT W4.5mm 磷铜镀金G/F	/	PCS
ITEM	PART NAME	DESCRIPTION	QUAY	UNIT

	单位 UNIT	mm	泰华电子有限公司 TaiHua Electronics Co., Ltd		
	比例 SCALE				
x.±0.5	x.*±	核准:	版本: A0	产品名称 Production name	PH1.27mm 排母 G/F SMT
.x±0.30	.x.*±	APPROVED BY	页次: 1/1	产品料号 Product No	
.xx±0.20	.xx.*±	CHECKED BY	日期:	客户料号 Client No	
.xxx±0.005	.xxx.*±	DRAWN BY			