



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: Wafer PA6I, UL94V-0  
PIN Phosphoric bronze Tin-plated  
Solder tad Phosphoric bronze Tin-plated

编 号	尺寸 (mm)		
	A	B	C
A1002WF-02A	1.00	3.20	4.00
A1002WF-03A	2.00	4.20	5.00
A1002WF-04A	3.00	5.20	6.00
A1002WF-05A	4.00	6.20	7.00
A1002WF-06A	5.00	7.20	8.00
A1002WF-07A	6.00	8.20	9.00
A1002WF-08A	7.00	9.20	10.00
A1002WF-09A	8.00	10.20	11.00
A1002WF-10A	9.00	11.20	12.00
A1002WF-11A	10.00	12.20	13.00
A1002WF-12A	11.00	13.20	14.00
A1002WF-20A	19.00	21.20	22.00

	单位	mm	<p><b>泰华电子有限公司</b> <i>TaiHua Electronics Co., Ltd</i></p>
	比例	1:1	
核准:	核准:	版本:	A0
审核:	审核:	页次:	1/1
制图:	封文辉	日期:	
比例	1:1	产品名称	1.0超薄贴片
比例	1:1	产品料号	TH-A1002-WF-NA
比例	1:1	客户料号	
比例	1:1	客户No	