



PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 1A AC, DC
  - 2、Voltage Rating: 125V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 100MΩ Min
  - 6、Withstanding Voltage: 500V AC/minute
  - 7、Material: Wafer LCP, UL94V-0
- PIN Brass Tin-plated  
Solder tad Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A1251-03AB	2.50	8.60
A1251-04AB	3.75	9.85
A1251-05AB	5.00	11.10
A1251-06AB	6.25	12.35



X. ±0.5	X*±
. X±0.30	. X*±
. XX±0.20	. XX*±
. XXX±0.009, XXX*±	

单位 UNIT	mm
比例 SCALE	
核准: APPROVED BY	
审核: CHECKED BY	
制图: DRAWN BY	封文辉
	2022.10.06

版本: A0	版本: A0	产品名称 Production name	1.25立脚 WAFER SMT TYPE
页次: 1/1	页次: 1/1	产品料号 Product No	TH-A1251-NNAB(闭口)
日期:	日期:	客户料号 Client No	

泰华电子有限公司  
**TaiHua Electronics Co., Ltd**