



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 7A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1500V AC/minute
  - 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A5801-02A	5.08	10.16
A5801-03A	10.16	15.24
A5801-04A	15.24	20.32
A5801-05A	20.32	25.40
A5801-06A	25.40	30.48
A5801-07A	30.48	35.56
A5801-08A	35.56	40.64
A5801-09A	40.64	45.72
A5801-10A	45.72	50.80
A5801-11A	50.80	55.88
A5801-12A	55.88	60.96
A5801-20A	96.52	101.60



单位 UNIT  
mm

比例 SCALE  
x:±  
x.±0.5  
.x±0.30  
.xx±0.20  
.xxx±0.005, xxx %

泰华电子有限公司  
**TaiHua Electronics Co., Ltd**

版本: A0  
日期: 1/1

产品名称: 5.08直针 WAFER DIP TYPE  
产品料号: TH-A5081-NA  
客户料号: 客户料号

制图: 封文馨  
日期: 2022.3.1