



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 9A AC, DC
  - 2、Voltage Rating: 600V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1500V AC/minute
  - 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A4250-2X01A	5.40	
A4250-2X02A	4.20	9.60
A4250-2X03A	8.40	13.80
A4250-2X04A	12.60	18.00
A4250-2X05A	16.80	22.20
A4250-2X06A	21.00	26.40
A4250-2X07A	25.20	30.60
A4250-2X08A	29.40	34.80
A4250-2X09A	33.60	39.00
A4250-2X10A	37.80	43.20
A4250-2X11A	42.00	47.40
A4250-2X12A	46.20	51.60

深圳市泰华电子有限公司  
TaiHua Electronics Co., Ltd

	X ± 0.5	X ± 0.5
	X ± 0.30	X ± 0.30
	XX ± 0.20	XX ± 0.20
	.XXX ± 0.005	.XXX ± 0.005

单位 UNIT	mm	版本: VERSION	A0	产品名称 Product Name	5569 双排直插 WATER DIP TYPE
比例 SCALE		核准: APPROVED BY		产品料号 Product No	TH-A4250-2XNA
		审核: CHECKED BY	1/1	客户料号 Client No	
		制图: DRAWN BY	封文辉 2022.12.05		