



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000mΩ Min
- 6、Withstanding Voltage: 800V AC/minute
- 7、Material:Housing:Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A2023-2X02Y	2.00	6.00
A2023-2X03Y	4.00	8.00
A2023-2X04Y	6.00	10.00
A2023-2X05Y	8.00	12.00
A2023-2X06Y	10.00	14.00
A2023-2X07Y	12.00	16.00
A2023-2X08Y	14.00	18.00
A2023-2X09Y	16.00	20.00
A2023-2X10Y	18.00	22.00
A2023-2X11Y	20.00	24.00
A2023-2X12Y	22.00	26.00
A2023-2X22Y	42.00	46.00



X ±0.5 X ±

. X ±0.30 . X ±

. XX ±0.20 . XX ±

. XXX ±0.005 . XXX ±

单位 UNIT mm  
比例 SCALE  
核准: APPROVED BY  
审核: CHECKED BY  
制图: 封文辉  
DRAWN BY 2022.9.5

版本: A0  
页次: 1/1  
日期:

**泰华电子有限公司**  
**TaiHua Electronics Co., Ltd**

产品名称 PHDC带钩孔座  
产品料号 TH-A2023-2XNY  
客户料号 Client No