


- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 800V AC/minute
  - 7、Material: Wafer PA46, UL94V-0  
PIN Brass Tin-plated

| 编号          | 尺寸 (mm) |       |
|-------------|---------|-------|
|             | A       | B     |
| A2004-2X02A | 2.00    | 6.00  |
| A2004-2X03A | 4.00    | 8.00  |
| A2004-2X04A | 6.00    | 10.00 |
| A2004-2X05A | 8.00    | 12.00 |
| A2004-2X06A | 10.00   | 14.00 |
| A2004-2X07A | 12.00   | 16.00 |
| A2004-2X08A | 14.00   | 18.00 |
| A2004-2X09A | 16.00   | 20.00 |
| A2004-2X10A | 18.00   | 22.00 |
| A2004-2X11A | 20.00   | 24.00 |
| A2004-2X12A | 22.00   | 26.00 |
| A2004-2X20A | 38.00   | 42.00 |



|       |             |
|-------|-------------|
| 单位    | mm          |
| 比例    |             |
| SCALE |             |
| 核准:   | APPORVED BY |
| 审核:   | CHECKED BY  |
| 制图:   | DRAWN BY    |

**深圳市泰华电子有限公司**  
**TaiHua Electronics Co., Ltd**

|       |                      |
|-------|----------------------|
| 单位    | mm                   |
| 比例    |                      |
| SCALE |                      |
| 核准:   | APPORVED BY          |
| 审核:   | CHECKED BY           |
| 制图:   | DRAWN BY             |
| 版本:   | A0                   |
| 图次:   | 1/1                  |
| 产品名称  | PHD直针 WAFER DIP TYPE |
| 产品料号  | TH-A2004-2XNA        |
| 客户料号  |                      |
| 日期:   |                      |
| 客户名称  | Client No            |