


PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 7A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 1500V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A3961-02A	3.96	7.92
A3961-03A	7.92	11.88
A3961-04A	11.88	15.84
A3961-05A	15.84	19.80
A3961-06A	19.80	23.76
A3961-07A	23.76	27.72
A3961-08A	27.72	31.68
A3961-09A	31.68	35.64
A3961-10A	35.64	39.60
A3961-11A	39.60	43.56
A3961-12A	43.56	47.52



单位  
UNIT  
mm

深圳市泰华电子有限公司  
**TaiHua Electronics Co., Ltd**

X. ±0.5	X*±
. X±0.30	. X*±
. XX±0.20	. XX*±
. XXX±0.005, XXX*±	

批准: APPROVED BY  
审核: CHECKED BY  
制图: DRAWN BY  
日期: 2022.9.5

版本: A0  
页次: 1/1  
产品名称: Production name  
产品料号: Product No  
客户料号: Client No