


PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
  - 2、Voltage Rating: 100V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 500MΩ Min
  - 6、Withstanding Voltage: 500V AC/minute
  - 7、Material: Wafer Nylon 6T, UL94V-0
- PIN Brass Tin-plated  
Solder tad Phosphoric copper Tin-plated

编号	尺寸 (mm)	
	A	B
A1500WF-02A	1.50	6.00
A1500WF-03A	3.00	7.50
A1500WF-04A	4.50	9.00
A1500WF-05A	6.00	10.50
A1500WF-06A	7.50	12.00
A1500WF-07A	9.00	13.50
A1500WF-08A	10.50	15.00
A1500WF-09A	12.00	16.50
A1500WF-10A	13.50	18.00
A1500WF-11A	15.00	19.50
A1500WF-12A	16.50	21.00
A1500WF-20A	28.50	33.00



X.±0.5

.X±0.30

.XX±0.20

.XXX±0.009, XXX ±

单位	mm
比例	
SCALE	

核准:	版本:	A0	产品名称	泰华电子有限公司
APPORVED BY	TH-AL500WF-NA	Production name	ZH贴片 WAFER SMT TYPE	
审核:	页次:	1/1	产品料号	TH-AL500WF-NA
CHECKED BY	日期:		客户料号	
DRAWN BY	2022.9.6	封装图	客户料号	
		2022.9.6	Client No	

泰华电子有限公司  
TaiHua Electronics Co., Ltd