


PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 1A AC, DC
 - 2、Voltage Rating: 100V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 500MΩ Min
 - 6、Withstanding Voltage: 500V AC/minute
 - 7、Material: Wafer PBT/PA46 White/Beige, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A1500-02AW	1.50	4.50
A1500-03AW	3.00	6.00
A1500-04AW	4.50	7.50
A1500-05AW	6.00	9.00
A1500-06AW	7.50	10.50
A1500-07AW	9.00	12.00
A1500-08AW	10.50	13.50
A1500-09AW	12.00	15.00
A1500-10AW	13.50	16.50
A1500-11AW	15.00	18.00
A1500-12AW	16.50	19.50
A1500-20AW	28.50	31.50



X. ±0.5	X*±
. X±0.30	. X*±
. XX±0.20	. XX*±
. XXX±0.008	. XXX*±

单位 UNIT	mm
比例 SCALE	
批准: APPROVED BY	版本: A0
审核: CHECKED BY	图例: 封文辉
日期:	日期:
客户料号 Client No	产品名称 Production name
	ZH弯针 WAFER DIP TYPE

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

版本 REV	变更日期 CHANGE DATE	变更人 TAIHWAE	备注 REMARK
1.0			