


TCXO UNIT WITH CLIPPED SINE WAVE OUTPUT IN SMD 7.0x5.0MM CERAMIC SEAM SEAL PACKAGE.

### PRODUCT FEATURES

- 7.0x5.0x1.4 with 4 solder pads.
- Tight stabilities over temperature range.
- RoHS compliant, LEAD-FREE, HALOGEN-FREE and REACH compliant.

### PRODUCT PHOTO (NOT IN SCALE)



### APPLICATIONS


- WiMAX / WLAN / Ethernet
- Telecommunication
- Mobil applications

### PRODUCT SPECIFICATIONS

PARAMETER	SUPPLY VOLTAGE			REMARKS
	1.8V	2.5V	2.8/ 3.0/ 3.3V	
Frequency range	10 ~ 52MHz			--
Frequency tolerance	±1.0ppm			Initial tol. @+25°C
Frequency stability	±0.5ppm / ±1.0; 1.5ppm / ±2.0ppm; ±2.5ppm			See note below table
Operating temperature range	-10 to +70°C / -30 to +85°C / -40 to +85°C			In combination to above stabilities.
Aging per year	±1.0ppm			@+25°C
Output waveform	Clipped sine wave			--
Output load	10kΩ/10pF			--
Output voltage level	0.8Vp-p			Minimum
Phase noise (example 19.2MHz)	-115dBc/Hz / -135dBc/Hz / -148dBc/Hz			@100Hz / 1kHz / 10kHz
Phase jitter RMS	<1ps			12kHz ≤ Fj ≤ 20MHz
Supply current	5mA	7mA	10mA	@10kΩ/10pF

Note: Frequency stability is the frequency deviation over temperature range in reference to +25°C

### PACKAGE OUTLINE / DIMENSIONS



### PACKAGING INFORMATION

- Tape & Reel compliant to EIA-481.
- Embossed carrier width 12mm.
- Component pitch in carrier 8mm.
- Reel diameter 180mm.
- QTY per reel: 1,000pcs

### RECOMMENDED REFLOW PROFILE

